



IF IT'S SELLEYS IT WORKS™

Technical Data Sheet

Grout Stain Whitener

Updated
11/10/2010

DESCRIPTION

Grout Stain Whitener is a paint formula developed for grout surfaces intended to cover stains and discolouration. Can also cover coloured grout to appear as a new white grout surface. Seals grout to prevent future mould growth and contains a fungicide to add further protection from regrowth.

SIZES AVAILABLE

280g squeeze tube with foam applicator, white in colour only.

USES

Grout Stain Whitener can be used on grout between non-porous tiles in kitchens, bathrooms and laundries.

TECHNICAL FEATURES

- Covers and whitens stains
- Breaks the mould cycle
- Protects grout from stains, contains a fungicide to help prevent mould regrowth.
- Enables you to change the colour of grey or other coloured grout

TECHNICAL DETAILS	
Appearance:	Appears as a lump free, white paste. Dry film has course texture.
SG:	1.32-1.36
Viscosity:	1000 – 1600 ps (HAF 5 TE)

HOW TO USE

- Clean tiled area and grout thoroughly.
- Ensure that the area is dry.
- Wearing gloves, apron and old clothing is recommended.
- Press foam applicator firmly against grout and apply even pressure to the tube while moving applicator along grout lines
- Allow to dry for at least 30minutes, then check if sufficiently dry by wiping over with a damp cloth. If product is not dry, allow a longer drying time (no more than 2 hours).
- When dry, remove excess with a lint free damp cloth or sponge, wiping diagonally across the grout line. A Selleys Super Cloth is ideal.
- Reapply where too little product was applied or too much was wiped off.
- After use, rinse sponge tilting downwards under tap. Blot dry and replace firmly until next use.
- Allow at least 5 hours before treated area is exposed to water.

COVERAGE:

Coverage varies depending on size of tiles: As a guide one pack will cover:

- 15sq metres if the tile size is 200mm x 200mm
- 7.5 sq metres if tile size is 50mm x 50mm

LIMITATIONS

Do not use on unglazed or porous tiles and stone.

Not recommended for tiles with intricate patterns or grooves from which the product may be difficult to remove.

WARNINGS/FIRST AID & SHIPPING INFORMATION: Refer to the **MSDS** section located on the Selleys Website.



Ph: AU - 1300 555 205
Ph: NZ - 0800 735 539
Website - www.selleys.com.au
Email - selleys.customer.service@selleys.com.au
Head Office: 1 Gow Street, Padstow NSW 2211 AU

Page | 1

© 2010 Selleys Pty Limited
ABN 67 000 049 427

All information contained in this Product Information Sheet is as accurate and up-to-date as possible. Products can be expected to perform as indicated in this Sheet, so long as application procedures are followed as recommended. However, there are no expressed or implied warranties set out in this information other than those implied by Commonwealth, State or Territory Legislation.