



Cordless Worklight  
DML813 / DML814

Satisfy Professional's Needs



Max luminous flux  
**3,000 lm**

Max Height  
**2,240 mm**

**IP55**

certified weather  
and dust resistance

**DML813**

[ Spot lighting ]



**DML814**

[ Spot lighting ]



[ Area lighting ]



**18V**  
LITHIUM-ION



### Continuous run time (with BL1850B)

High	Medium	Low
<b>3.0 h</b>	<b>5.5 h</b>	<b>10 h</b>

### 3 brightness settings

High	Medium	Low
<b>3,000 lm</b>	<b>1,700 lm</b>	<b>900 lm</b>

Pivoting range of light head for Spot lighting



right and left  
**115°**

up and down  
**110°**

Pivoting range of 3 small light heads for area lighting



up and down  
**90°**  
DML814 only

### Foldable into a compact size for simple storage and transport



**1,000 mm**

Push the unlock button to expand / fold the tripod base.



#### Shoulder belt

Attachable to the worklight or tool bag for comfortable carrying of the worklight



### Accessories

#### Tool Bag



#### Shoulder Belt



**2,240 mm**



The height of light head can be adjusted steplessly



**1,250 mm**

**18V**  
**LITHIUM-ION**

#### DML814

#### Two lighting modes

Spot lighting / Area lighting

#### Battery capacity warning function

automatically notifies the user about reduction in battery capacity with the decrease of illuminance (Only one LED is on for notification).



#### DML813

Spot lighting



#### Easy installation and removal of battery



The battery port is located at the middle height of the worklight so that the user need not bend down to access the battery.

#### Padlock hole for battery theft protection




\*Padlock not included

#### Three hook holes for the shoulder belt

Two hook holes are located on the carrying handle beside the battery, and one on the end of a tripod leg.

#### Tripod fixing hole



The tripod can be firmly secured to the ground with a screw or peg.

### Cordless Worklight

### DML813 / DML814



Carrying Case

Standard Equipment:  
Shoulder Belt

#### Run Time (hrs)

#### Illuminance

(High / Mid / Low)

#### Luminous Flux Dimensions (L x W x H)

#### Net weight

w/ BL1850(B) Low / Mid / High: 10 / 5.5 / 3  
at 1m from the light source: 1,250 / 750 / 400 lx  
at 3m from the light source: 130 / 80 / 40 lx  
at 5m from the light source: 50 / 30 / 15 lx  
High / Mid / Low: 3,000 / 1,700 / 900 lm  
Folding Position:  
260x216x1,000 mm (10-1/4"x8-1/2"x39-3/8")  
Operating Position (Max Height):  
573x658x1,250-2,240 mm (22-1/2"x26"x49-1/4"-88")  
DML813: 7.0 - 7.7 kg (15.4 - 17.0 lbs.)  
DML814: 7.2 - 7.9 kg (15.9 - 17.4 lbs.)

Battery & Charger Sold Separately

The weight may differ depending on the attachment(s), including the battery cartridge.  
Items of standard equipment and specifications may vary by country or area.

### Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348  
Phone : +65-6546-8700 Fax : +65-6546-8711  
Email : msgproductteam@makita.com.sg  
Website : www.makita.com.sg  
Facebook : www.facebook.com/MakitaSG



VISIT OUR WEBSITE

PRINTED IN SINGAPORE