



Optimum power supply system and Optimum charging system

The XGT range of tools and batteries come with a built-in program, providing digital communication between the battery and tool. Allowing not only for the battery to talk with tool but also the tool to talk to the battery. Battery technology and motor engineering that work together for optimum performance.



Built Tough

High durability specifications specially designed for 40Vmax Li-Ion batteries



Optimum charging system

Auto maintenance system with two cooling fans for providing more optimum fast charging

Tool ↔ Battery ↔ Battery Charger
Digital communication

Accessories

Grip assembly set

Part No. 191E41-8



Bit holder

Part No. 452947-8



Charging Time Reference

	DC40RA (191E08-6)	DC40RC (191M92-9)
BL4020 2.0Ah (191L29-0)	22min	30min
BL4025 2.5Ah (191B36-3)	28min	38min
*1BL4040 4.0Ah (191B26-6)	45min	67min
*1BL4050F 5.0Ah (191L47-8)	50min	85min

*1 Recommended battery

Cordless Hammer Driver Drill	HP002G 13 mm (1/2")																																				
Cordless Driver Drill	DF002G 13 mm (1/2")																																				
<ul style="list-style-type: none"> Variable Speed Built-in Job Light Brake Carrying Case Reversing Mechanical 2-Speed Keyless Chuck Torque Setting 21 Constant Speed 	<table border="1"> <thead> <tr> <th></th> <th>HP002G</th> <th>DF002G</th> </tr> </thead> <tbody> <tr> <td>Capacity</td> <td>Steel / Wood (Auger Bit) / Wood (Self-Feed Bit) / Wood (Hole Saw) / Masonry: 13 / 38 / 38 / 51 / 13 mm (1/2 / 1-1/2 / 1-1/2 / 2 / 1/2") 1.5 - 13 mm (1/16 - 1/2")</td> <td>Steel / Wood (Auger Bit) / Wood (Self-Feed Bit) / Wood (Hole Saw): 13 / 38 / 38 / 51 mm (1/2 / 1-1/2 / 1-1/2 / 2") 1.5 - 13 mm (1/16 - 1/2")</td> </tr> <tr> <td>Chuck Capacity</td> <td>1.5 - 13 mm (1/16 - 1/2")</td> <td>1.5 - 13 mm (1/16 - 1/2")</td> </tr> <tr> <td>Impacts Per Minute (IPM)</td> <td>High / Low: 0 - 33,000 / 0 - 9,000</td> <td>-</td> </tr> <tr> <td>No Load Speed (RPM)</td> <td>High / Low: 0 - 2,200 / 0 - 600</td> <td>High / Low: 0 - 2,200 / 0 - 600</td> </tr> <tr> <td>Max Fastening Torque</td> <td>Hard / Soft: 64 / 30 N·m (570 / 270 in.lbs.)</td> <td>Hard / Soft: 64 / 30 N·m (570 / 270 in.lbs.)</td> </tr> <tr> <td>Max Lock Torque</td> <td>65 N·m (580 in.lbs.)</td> <td>65 N·m (580 in.lbs.)</td> </tr> <tr> <td>Vibration Level</td> <td>Impact Drilling into Concrete: 9.0 m/s² Drilling into Metal: 2.5 m/s² or less</td> <td>Drilling into Metal: 2.5 m/s² or less</td> </tr> <tr> <td>Sound Pressure Level</td> <td>87 dB(A)</td> <td>78 dB(A)</td> </tr> <tr> <td>Sound Power Level</td> <td>98 dB(A)</td> <td>-</td> </tr> <tr> <td>Dimensions (L x W x H)</td> <td>w/o Battery: 174 x 86 x 215 mm (6-7/8 x 3-3/8 x 8-1/2") w/ BL4040: 174 x 86 x 272 mm (6-7/8 x 3-3/8 x 10-3/4")</td> <td>w/o Battery: 164 x 86 x 215 mm (6-1/2 x 3-3/8 x 8-1/2") w/ BL4040: 164 x 86 x 272 mm (6-1/2 x 3-3/8 x 10-3/4")</td> </tr> <tr> <td>Net weight</td> <td>2.0 - 2.6 kg (4.4 - 5.7 lbs.)</td> <td>1.9 - 2.5 kg (4.2 - 5.5 lbs.)</td> </tr> </tbody> </table>		HP002G	DF002G	Capacity	Steel / Wood (Auger Bit) / Wood (Self-Feed Bit) / Wood (Hole Saw) / Masonry: 13 / 38 / 38 / 51 / 13 mm (1/2 / 1-1/2 / 1-1/2 / 2 / 1/2") 1.5 - 13 mm (1/16 - 1/2")	Steel / Wood (Auger Bit) / Wood (Self-Feed Bit) / Wood (Hole Saw): 13 / 38 / 38 / 51 mm (1/2 / 1-1/2 / 1-1/2 / 2") 1.5 - 13 mm (1/16 - 1/2")	Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")	1.5 - 13 mm (1/16 - 1/2")	Impacts Per Minute (IPM)	High / Low: 0 - 33,000 / 0 - 9,000	-	No Load Speed (RPM)	High / Low: 0 - 2,200 / 0 - 600	High / Low: 0 - 2,200 / 0 - 600	Max Fastening Torque	Hard / Soft: 64 / 30 N·m (570 / 270 in.lbs.)	Hard / Soft: 64 / 30 N·m (570 / 270 in.lbs.)	Max Lock Torque	65 N·m (580 in.lbs.)	65 N·m (580 in.lbs.)	Vibration Level	Impact Drilling into Concrete: 9.0 m/s ² Drilling into Metal: 2.5 m/s ² or less	Drilling into Metal: 2.5 m/s ² or less	Sound Pressure Level	87 dB(A)	78 dB(A)	Sound Power Level	98 dB(A)	-	Dimensions (L x W x H)	w/o Battery: 174 x 86 x 215 mm (6-7/8 x 3-3/8 x 8-1/2") w/ BL4040: 174 x 86 x 272 mm (6-7/8 x 3-3/8 x 10-3/4")	w/o Battery: 164 x 86 x 215 mm (6-1/2 x 3-3/8 x 8-1/2") w/ BL4040: 164 x 86 x 272 mm (6-1/2 x 3-3/8 x 10-3/4")	Net weight	2.0 - 2.6 kg (4.4 - 5.7 lbs.)	1.9 - 2.5 kg (4.2 - 5.5 lbs.)
	HP002G	DF002G																																			
Capacity	Steel / Wood (Auger Bit) / Wood (Self-Feed Bit) / Wood (Hole Saw) / Masonry: 13 / 38 / 38 / 51 / 13 mm (1/2 / 1-1/2 / 1-1/2 / 2 / 1/2") 1.5 - 13 mm (1/16 - 1/2")	Steel / Wood (Auger Bit) / Wood (Self-Feed Bit) / Wood (Hole Saw): 13 / 38 / 38 / 51 mm (1/2 / 1-1/2 / 1-1/2 / 2") 1.5 - 13 mm (1/16 - 1/2")																																			
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")	1.5 - 13 mm (1/16 - 1/2")																																			
Impacts Per Minute (IPM)	High / Low: 0 - 33,000 / 0 - 9,000	-																																			
No Load Speed (RPM)	High / Low: 0 - 2,200 / 0 - 600	High / Low: 0 - 2,200 / 0 - 600																																			
Max Fastening Torque	Hard / Soft: 64 / 30 N·m (570 / 270 in.lbs.)	Hard / Soft: 64 / 30 N·m (570 / 270 in.lbs.)																																			
Max Lock Torque	65 N·m (580 in.lbs.)	65 N·m (580 in.lbs.)																																			
Vibration Level	Impact Drilling into Concrete: 9.0 m/s ² Drilling into Metal: 2.5 m/s ² or less	Drilling into Metal: 2.5 m/s ² or less																																			
Sound Pressure Level	87 dB(A)	78 dB(A)																																			
Sound Power Level	98 dB(A)	-																																			
Dimensions (L x W x H)	w/o Battery: 174 x 86 x 215 mm (6-7/8 x 3-3/8 x 8-1/2") w/ BL4040: 174 x 86 x 272 mm (6-7/8 x 3-3/8 x 10-3/4")	w/o Battery: 164 x 86 x 215 mm (6-1/2 x 3-3/8 x 8-1/2") w/ BL4040: 164 x 86 x 272 mm (6-1/2 x 3-3/8 x 10-3/4")																																			
Net weight	2.0 - 2.6 kg (4.4 - 5.7 lbs.)	1.9 - 2.5 kg (4.2 - 5.5 lbs.)																																			

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



VISIT OUR WEBSITE

PRINTED IN SINGAPORE



No load speed
High speed mode
2,200
min⁻¹

High speed and Compact



Cordless Hammer Driver Drill
HP002G
13 mm (1/2")



Cordless Driver Drill
DF002G
13 mm (1/2")

Max lock torque
65 N·m

Net weight*
1.9 kg

*model: DF002G / Battery: BL4020



High speed and Compact

All metal gear construction



BL MOTOR High power Brushless motor



Wood \varnothing 38 mm



Steel \varnothing 13 mm



Spiral step drill \varnothing 22 mm



Tap drill M10

Increased work speed

Rotation speed becomes faster providing increased work speed especially in a light duty application like drilling with a 7/8" ship auger bit.

Increased maneuverability

thanks to compact design

DF002G

164 mm

[HP002G / 174mm]



Cordless Hammer Driver Drill
HP002G



Cordless Driver Drill
DF002G



Single sleeve keyless chuck

Twin LED job light with preglow and afterglow functions



Variable speed control by trigger

XGT
40V^{Li-ion}max

Powered by 40Vmax XGT Li-Ion battery

Mechanical 2-speed gearing



Aluminum gear housing

Belt clip

XPT eXtreme Protection Technology

