

Satisfy Professional's Needs



# Cordless Angle Grinder Series

DGA413 100 mm (4")

DGA417 100 mm (4")

DGA513 125 mm (5")

DGA517 125 mm (5")



**VARIABLE SPEED CONTROL**





### Slide Switch Type

Standard equipment : Grinding Wheel, Wheel Cover, Side Grip, Lock Nut Wrench, Battery, Charger

- Variable Speed
- Brake
- Soft Start
- Dust Collecting
- Carrying Case

	DGA413	DGA513
Wheel Diameter	100 mm (4")	125 mm (5")
No Load Speed (RPM)	3,000 - 8,500	3,000 - 8,500
Vibration Level (Surface Grinding)	4.0 m/s <sup>2</sup>	6.0 m/s <sup>2</sup>
Vibration Level (Disc Sanding)	2.5 m/s <sup>2</sup> or less	2.5 m/s <sup>2</sup> or less
Sound Pressure Level	80 dB(A)	79 dB(A)
Dimensions (L x W x H) with BL1815N / BL1820B:	368x117x147 mm (14-1/2"x4-5/8"x5-3/4")	368x140x151 mm (14-1/2"x5-1/2"x5-15/16")
Dimensions (L x W x H) with BL1830B / BL1840B / BL1850B / BL1860B:	382x117x147 mm (15"x4-5/8"x5-3/4")	382x140x151 mm (15"x5-1/2"x5-15/16")
Net weight	DGA413: 2.2 - 2.8 kg (4.9 - 6.2 lbs.)	DGA513: 2.4 - 3.0 kg (5.2 - 6.7 lbs.)



### Paddle Switch Type

Standard equipment : Grinding Wheel, Wheel Cover, Side Grip, Lock Nut Wrench, Battery, Charger

- Variable Speed
- Brake
- Soft Start
- Dust Collecting
- Carrying Case

	DGA417	DGA517
Wheel Diameter	100 mm (4")	125 mm (5")
No Load Speed (RPM)	3,000 - 8,500	3,000 - 8,500
Vibration Level (Surface Grinding)	4.5 m/s <sup>2</sup>	5.5 m/s <sup>2</sup>
Vibration Level (Disc Sanding)	2.5 m/s <sup>2</sup> or less	2.5 m/s <sup>2</sup> or less
Sound Pressure Level	80 dB(A)	79 dB(A)
Dimensions (L x W x H) with BL1815N / BL1820B:	368x117x146 mm (14-1/2"x4-5/8"x5-3/4")	368x140x151 mm (14-1/2"x5-1/2"x6")
Dimensions (L x W x H) with BL1830B / BL1840B / BL1850B / BL1860B:	382x117x146 mm (15"x4-5/8"x5-3/4")	382x140x151 mm (15"x5-1/2"x6")
Net weight	DGA417: 2.2 - 2.9 kg (4.9 - 6.3 lbs.)	DGA517: 2.4 - 3.1 kg (5.2 - 6.7 lbs.)

		BL1815N 1.5Ah (196449-1)	BL1830B 3.0Ah (197599-5)	BL1850B 5.0Ah (197280-8)	BL1860B 6.0Ah (197422-4)
Fast Charger <b>DC18RC</b> (195586-8)	Two port multi Fast Charger <b>DC18RD</b> (196934-4)	<b>15 min</b>	<b>22 min</b>	<b>45 min</b>	<b>55 min</b>
Standard Charger <b>DC18SD</b> (194534-4)		<b>30 min</b>	<b>60 min</b>	<b>110 min</b>	<b>130 min</b>

### Product Comparison List

Model No.		No load speed (rpm)	Switch	BL motor	AFT	ADT	Brake	XPT	Anti-restart function
100mm	125mm								
DGA413 <b>NEW</b>	DGA513 <b>NEW</b>	3,000 - 8,500	Slide	●	●	●	●	●	●
DGA406	DGA506	8,500	Slide	●	●	●	●	●	●
DGA404		8,500	Slide	●	●	●	●	●	●
DGA417 <b>NEW</b>	DGA517 <b>NEW</b>	3,000 - 8,500	Paddle	●	●	●	●	●	●
DGA408	DGA508	8,500	Paddle	●	●	●	●	●	●
DGA405		8,500	Paddle	●	●	●	●	●	●

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

### Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348  
 Phone : +65-6546-8700 Fax : +65-6546-8711  
 Email : msgproductteam@makita.com.sg  
 Website : www.makita.com.sg  
 Facebook : www.facebook.com/MakitaSG



VISIT OUR WEBSITE

Item code : Z-10409

PRINTED IN SINGAPORE