



V-notch in base plate helps easy tracing of cutting line.



Dust collector

catches dust that drops through the base of base cover.

Dust connector assembly

connectable to vacuum cleaner.

LED job light

brightly illuminates the cut line for easy cutting of workpiece in the dark place.



Cutting depth adjustment



- Cutting depth can be adjusted to drywall thickness.
- Prevent accidental breakage of wires

Blade cover

protects drywall surfaces from damage/ scratches.







Blades



Compatible with both special blades for this drywall saw and option snap-off blades.

■ Li-ion Battery & Charging Time Reference

*with Battery fuel gauge	*BL1040B	*BL1020B	BL1015
	10.8V 4.0Ah	10.8V 2.0Ah	10.8V 1.5Ah
Charging DC10MC	60	30	22
	min	min	min
	130	70	50
	min	min	min

Cordless Drywall Saw SD100D

Strokes Per Minute (SPM) 0 - 6,000 Length of Stroke 6 mm (1/4") Variable Speed Drywall: 30mm (1-3/16") Wood: 15 mm (9/16") Orbital Cutting Max Output **Dust Collecting** Cutting Drywall (thickness 30mm): 3.0 m/s² Cutting Chip Board (thickness 15mm): 5.5 m/s² Vibration Level Built-in Job Light Sound Pressure Level 77 dR(A) 239x79x266mm (9-3/8"x3-1/8"x10-1/2") Dimensions (L x W x H) BL1015 / BL1020B : 1.5 kg (3.3 lbs) BL1040B : 1.6kg (3.6lbs) Carrying Case Net weight

Standard Equipment: Blade, Blade cover, Base cover, Hex Wrench, Battery, Charger

weight according to EPTA-Procedure 01/ver.2.1 Items of standard equipment and specifications may vary by country or area.

Item code: Z-10333

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348 Phone: +65-6546-8700 Fax: +65-6546-8711

Email: salesadv@makita.com.sg Website: www.makita.com.sg

Facebook: www.facebook.com/MakitaSG





VISIT OUR WEBSITE