



In new model **REGINA+** the old C profile has been changed with a strong high-performance box one. The ladder with a load has a lower torsion and it is more resistant to operator's movements and weight. Welding undergoes a lower effort assuring a long lasting structure. It weighs 1 kg more than the standard Regina but all the other dimensions are the same. Also the hinge is new and it has been reinforced.

- Polypropylene heavy duty platform (30 x 25,5 cm) with safety blocking device
- Ergonomic reinforced non-skid rubber feet
- Non-skid steps 8 cm
- Distance between steps 25 cm
- Guardrail height 60 cm
- Width when closed 15 cm
- Reinforcements under the longest steps
- Anti-opening straps (thickness mm 25)
- Thermo-shrinkable plastic package with showcard



from March 2013

TECHNICAL FEATURES

Steps n°	Closed m	Platform height m	Working height m	Base width cm	Weight Kg
3	1,45	0,69	2,54/2,74	44,00	5,2
4	1,70	0,92	2,76/2,96	47,00	6,2
5	1,95	1,16	3,00/3,20	49,00	6,6
6	2,20	1,39	3,23/3,43	51,00	7,4
7	2,45	1,61	3,46/3,66	54,00	8,8
8	2,70	1,85	3,69/3,89	56,50	10,0
10	3,20	2,30	4,15/4,35	61,50	12,0
12	3,70	2,77	4,50/4,80	66,50	14,2

Front frame section mm 80x25 (new profile)
Back section mm 40x20

On request:

- Anti-opening/closing rigid bars
- Heavy duty aluminium platform



New profile



New Hinges
in painted steel



Optional heavy duty aluminium platform and rigid bars



Tool-holder
cm 26x7x3