



# Comes with valve adapters

	Light	truck	Ca	ar	Trac	ctor	Bicy	/cle	Road	l bike	B	all	Beach ball	/ Swim ring
Valve shape							8		•		10	PL		
Adapter	American				British	French		For Balls		For Swim rings / Beach balls				
									Part No. TE	00000334	Part No. TE	00000335	Part No. TE	00000333
	Light truck tire Regular car tire			Tractor tire		Bicy	Bicycle Road bike tire		Ball		Beach ball			
Objects	size: 205/70R16size: 215/60R16 $0 \rightarrow 600 \text{kPa}$ $0 \rightarrow 250 \text{kPa}$ High speed modeHigh speed mode		size: 7-14 0→180kPa High speed mode		size: 26 inch 0→300kPa Low speed mode		size: 700x23C 0→700kPa High speed mode		size: 700x23C 0→90kPa Ball mode		size: 30cm High speed mode			
Conditions	<b>MP001G</b> (BL4040)	<b>DMP181</b> (BL1860B)	<b>MP001G</b> (BL4040)	<b>DMP181</b> (BL1860B)	<b>MP001G</b> (BL4040)	<b>DMP181</b> (BL1860B)	<b>MP001G</b> (BL4040)	<b>DMP181</b> (BL1860B)	<b>MP001G</b> (BL4040)	DMP181 (BL1860B)	<b>MP001G</b> (BL4040)	DMP181 (BL1860B)	MP001G (BL4040)	DMP18 (BL1860
Work speed (approx)	8 min 25 sec	9 min 40 sec	2 min 45 sec	3 min 30 sec	1 min 40 sec	1 min 50 sec	9 sec	9 sec	17 sec	18 sec	39 sec	39 sec	22 sec	25 sec
Work amount on a full battery charge (approx)	4 times	3 times	<b>19</b> times	14 times	32 times	25 times	780 times	500 times	125 times	110 times	310 times	230 times	140 times	120 times

# Cordless Inflator series





# Charging Time

MP001G						
	DC40RA Fast Charging	DC40RC				
		H				
<b>BL4020</b> 2.0Ah	<b>22</b> min	<b>30</b> min				
<b>BL4025</b> 2.5Ah	28min	<b>38</b> min				
<b>BL4040</b> 4.0Ah	45 min	<b>67</b> min				
<b>BL4050F</b> 5.0Ah	<b>50</b> min	<b>85</b> min				
DMP181						
10-	DC18RC Fast Charging	DC18SD				
<b>BL1815N</b> 1.5Ah	15 min	<b>30</b> min				
<b>BL1820B</b> 2.0Ah	24 min	45 min				
BL1830B 3.0Ah	<b>22</b> min	<b>60</b> min				
<b>BL1840B</b> 4.0Ah	36min	<b>90</b> min				
<b>BL1850B</b> 5.0Ah	45 min	110 min				
<b>BL1860B</b> 6.0Ah	55 min	130 min				

# Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348 Phone: +65-6546-8700 Fax: +65-6546-8711 Email : msgproductteam@makita.com.sg Website : www.makita.com.sg Facebook: www.facebook.com/MakitaSG



# MP001G / DMP181

3 ×

		MP001G	DMP181		
Electronic 3-Speed	Air Discharge Amount	200 kPa: 24 L/min	200 kPa: 22 L/min		
Electronic 3-speed	-	700 kPa: 12 L/min	700 kPa: 11 L/min		
Built-in Job Light	Max Air Pressure	1,110 kPa (161 PSI) [11.1 bar]	1,110 kPa (161 PSI) [11.1 bar]		
	Hose Length	65 cm (25-1/2")	65 cm (25-1/2")		
Carrying Case	Sound Pressure Level	71 dB(A)	70 dB(A)		
	Vibration Level	3.8 m/s <sup>2</sup>	3.6 m/s <sup>2</sup>		
	Dimensions (L x W x H)	w/BL4020/BL4025: 320 x 108 x	w/BL1815N/BL1820B:		
		231 mm (12-5/8 x 4-1/4 x 9-1/8")	297 x 108 x 231 mm		
		w/ BL4040: 329 x 108 x 231 mm	(11-3/4 x 4-1/4 x 9-1/8")		
		(13 x 4-1/4 x 9-1/8")	w/BL1830B/BL1840B/BL1850B		
		w/ BL4050F: 351 x 108 x 231 mm	/ BL1860B: 316 x 108 x 231 mm		
		(13-3/4 x 4-1/4 x 9-1/8")	(12-1/2 x 4-1/4 x 9-1/8")		
	Net Weight	2.9 - 3.5 kg (6.4 - 7.7 lbs.)	2.5 - 2.8 kg (5.5 - 6.2 lbs.)		
andard Equipment : Bri	tish Adapter, French Adapter	r, Ball Adapter, Swim Ring Adapter, I	Battery, Charger		

MP100D 12Vmax CXT Li-Ion Cordless Inflator

Max air pressure

**830** kPa

[121PSI]

Air Discharge

**10** L/min

[200kPa]

Net weight

**1.2** kg

with BL1016

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.



VISIT OUR WEBSITE 🚹 MakitaSG 🔍







# High pressure inflation upto 1,100 kPa.







Satisfy Professional's Needs









Thakita





# Max air pressure 1,110 kPa (161PSI) [11.1 bar]




[200kPa] L/min **Z4** L/min

# Digital pressure gauge with backlight

[200kPa]

• Easier to read, larger display

• Both current and target pressure values can be simultaneously displayed. Overheat warning lamp blinks, and the machine automatically turns off.




Inflation mode change button

# Ideal for inflating tires of trucks and large vehicles etc.



### **3 Inflation modes**



# Air release function

In case of over-inflation, or if user wants to reduce the air pressure of road bike tires according to road conditions, press and hold the air release button to release air.

> Air release button









LED job light for easy operation at dark places.

Storing hose The hose can be attached to the hose holder of the tool.

Adapter holder

# Inflating from partially full to full

<b>Objects Conditions</b>		r car tire 50kPa, High speed mode		r <b>uck tire</b> 00kPa, High speed mode	Medium truck tire size: 225/80R17.5, 700→800kPa, High speed mode		
Model (Battery)	MP001G (BL4040)	DMP181 (BL1860B)	MP001G (BL4040)	DMP181 (BL1860B)	MP001G (BL4040)	DMP181 (BL1860B)	
Work speed	<b>1.1</b> min	<b>1.3</b> min	<b>1.8</b> min	<b>1.9</b> min	<b>3</b> min	<b>3.7</b> min	
Work amount on a full battery charge	50 times	<b>35</b> times	22 times	<b>18</b> times	<b>13</b> times	9 times	





Backlight



**eXtreme Protection** Technology