



Brushless Motor realized faster rebar cutting



Cutting capacity range of 3-16_{mm} standard rebar





Cutting head rotates 360° to accommodate different cutting positions.



Protector prevents that cut pieces may fly off.



Spark free cutting of rebar and steel rod ideal for use in sensitive areas

Built-in LED light illuminates the work area

Ergonomic pistol grip handle with soft grip provides increased comfort on the job



Ø 3~16mm

Cutting speed

about

30% Faster *

Work Amount

about

20%UP*



*Compared to the current model (DSC162) (cut 16mm rebar)

Accessories Cutter blade set

Part No.: SC09002470





Hydraulic pressure oil

35mL	SC00000106
150mL	SC00000142



Cordless Steel Rod Cutter

DSC163

Carrying Case

 Cutting Capacity
 Dia.: 3 - 16 mm (1/8" - 5/8")

 Cutting Speed (sec)
 2.8

 Dimensions (L x W x H)
 360x108x276 mm

(14-1/8"x4-1/4"x10-7/8") **Net weight**6.9 kg (15.2 lbs.)

Standard Equipment :

Wrench, Hex Wrench, Oil 35ml

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348 Phone: +65-6546-8700 Fax: +65-6546-8711 Email: msgproductteam@makita.com.sg

Website: www.makita.com.sg Facebook: www.facebook.com/MakitaSG





VISIT OUR WEBSITE