

High power Portable Cut-off



Toolless adjustment of guide plate (LW1400 only)

allows for easy adjustment of the guide plate by simple handling

3 stage position change

0 to 45 degree angle adjustment



Change of saw head locking device from chain lock to pin lock (LW1400 only)

makes it easier to lock down the saw head for storage and transport.



Carry handle

for easy transport to job site



Shaft lock for easy replacement of abrasive cut-off wheel



Photo: LW1400





Cutting Capacity		
Form of materials	Miter angle	
	0°	45°
O D	D: ø127mm (2")	D: ø127mm (2")
← W → † H +	H x W: 102 x 194mm (4" x 7-5/8") 70 x 233mm (2-3/4" x 9-1/8")	H x W: 115 x 103mm (4-1/2" x 4-1/16")
H-W→ ↑ H	H x W: 119 x 119mm (4-11/16" x 4-11/16")	H x W: 106 x 106mm (4-3/16" x 4-3/16")
STS	S x S: 137 x 137mm, T: 10mm (5-3/8" x 5-3/8"	S x S: 100 x 100mm, T: 10mm

D: Diameter W: Width

H: Height S: Side

3/8")

(4" x 4", 3/8")

T: Thickness

Accessory

Abrasive cut-off wheel

For all ferrous materials (Steel,cast iron) and other hard metals. These items are available on request. Contact us for the minimum order quantity

Size (mm): 355x3x25.4 **Grit:** A36P G.F.Q'ty: 1.0G

Per pkg.	Part No.
5	A-89545-5
25	A-89545-25
5	A-89953-5
5	B-10730-5
25	B-10730-25
5	B-10665-5
25	B-10665-25

Double Reinforced Abrasive cut-off wheel

Size (mm): 355x3x25.4 B-16891-5 Grit: A30P B-16891-25 G.F.Q'ty: 2.0G



Portable Cut-off LW1400 / LW1401 355mm (14")

Double Insulation Standard Equipment:

Abrasive Cut-Off Wheel, Socket Wrench (LW1401only) Continuous rating Input Wheel diameter Hole dia. No load speed (rpm) Dimensions (L x W x H) Power supply cord

LW1400 2.200W 355mm (14") 25.4mm (1") 3,800 530x295x640mm (20-7/8"x11-5/8"x25-1/4") 17.0kg (37.5lbs)

2.5m (8.2ft)

LW1401 2.200W 355mm (14") 25.4mm (1") 3,800 500x290x620mm (19-3/4"x11-3/8"x24-3/8") 16.6kg (36.6lbs) 2.5m (8.2ft)

203

*weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348 Phone: +65-6546-8700 Fax: +65-6546-8711

Email: salesadv@makita.com.sq Website: www.makita.com.sg

Item code : Z-10291

PRINTED IN SINGAPORE