



Cordless Hammer Driver Drill Cordless Driver Drill HP488D / DF488D 13 mm (1/2")



Cordless Hammer
Driver Drill
HP488D



New Design



Cordless Driver
Drill
DF488D





Single sleeve keyless chuck

allows for easy bit installation / removal with one hand.

Mechanical 2-speed gearing

- High speed mode for speedy drilling in light duty applications
- Low speed mode for heavy duty applications requiring high torque



All metal gear construction

- ensures high transmission durability.
- with gear case completely covering gears for increased durability against dust



Push button type reverse switch

Variable speed control by trigger

Accessories

Hook

Part No. 346449-3



Bit holder

Part No. 452947-8



photo: HP488D

Cordless Hammer Driver Drill HP488D



Cordless Driver Drill DF488D



Charging Time

18V
Lithium-ion

DC18WA
Part No. 195424-4



BL1815G 1.5Ah
Part No. 198186-3



70 min

Cordless Hammer Driver Drill

HP488D 13 mm (1/2")

Cordless Driver Drill

DF488D 13 mm (1/2")

- Variable Speed
- Brake
- Reversing
- Mechanical 2-Speed
- Keyless Chuck
- Torque Setting 16
- Carrying Case

| | HP488D | DF488D |
|---------------------------------|--|--|
| Capacity | Steel / Wood / Masonry: 13 / 36 / 13 mm (1/2" / 1-7/16" / 1/2") 1.5 - 13 mm (1/16" - 1/2") | Steel: 13 mm (1/2") Wood: 36 mm (1-7/16") 1.5 - 13 mm (1/16" - 1/2") |
| Chuck Capacity | 1.5 - 13 mm (1/16" - 1/2") | - |
| Impacts Per Minute (IPM) | High / Low: 0 - 21,000 / 0 - 6,000 | - |
| No Load Speed (RPM) | High / Low: 0 - 1,400 / 0 - 400 | High / Low: 0 - 1,400 / 0 - 400 |
| Max Fastening Torque | Hard / Soft: 42 / 24 N·m (370 / 210 in.lbs.) | Hard / Soft: 42 / 24 N·m |
| Max Lock Torque | 38 N·m (340 in.lbs.) | 38 N·m (340 in.lbs.) |
| Vibration Level | Hammer Drilling into Concrete: 9.5 m/s ² Drilling into Metal: 2.5 m/s ² or less | - Drilling into Metal: 2.5 m/s ² or less |
| Sound Pressure Level | 81 dB(A) | 70 dB(A) or less |
| Sound Power Level | 92 dB(A) | - |
| Dimensions (L x W x H) | 239 x 83 x 240 mm (9-3/8 x 3-1/4 x 9-1/2") | 221 x 83 x 240 mm (8-3/4 x 3-1/4 x 9-1/2") |
| Net weight | 1.8 kg (4.0 lbs.) | 1.7 kg (3.7 lbs.) |

Standard Equipment : (+)(-) Bit, Battery, Charger

Weight, with battery cartridge, according to EPTA-Procedure 01/2014
Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



VISIT OUR WEBSITE

PRINTED IN SINGAPORE