

BOSS®

SOLO700

Certified to
EN 1004-1:2020



The rapid-build single person BoSS access tower - **ONE PERSON OPERATION**

- Designed to be quick and safe to assemble by one person
- Base unit forms trolley for convenient storage and transportation
- 0.7m x 1.3m compact base size fits through standard doorways
- Variable working heights up to 6.2m
- 0.25m rung pitch for versatile working height positions
- One piece aluminium folding toe board set
- Ideal for use in public buildings and retail locations
- Part of the BoSS 700 range for interchangeable flexibility



bossacesstowers.com

DO MORE WITH
BOSS®

SOLO⁷⁰⁰

The BoSS **SOLO⁷⁰⁰** access tower is simple to assemble and operate by one person. The access tower can be dismantled to a compact size for convenient store in its own rolling trolley made from the base unit and one platform for easy transportation. Tower platform heights range from 2.2m to 4.2m. The patented camlock guardrail frames means this tower uses less components than a traditional BoSS tower.



Component Code	Component Name	Weight (kg)
67011000	End Frame 4 Rung 1m (H) × 0.7m (W)	3.9
67030100	Camlock Guardrail Frame 1.3m (W)	5.0
67050100	Aluminium Toe Board 1.3m (L)	4.4
35651300	Horizontal Brace 1.3m (L)	1.6
33551300	Adjustable leg	1.1
32842300	150mm (6") Castor	3.3
67060100	Assembly Bracket	2.3
67070100	Trapdoor Deck 1.3m (L)	9.8
67020100	Folding Base Unit 1.3m (W)	10.4
67040100	SP4 Telescopic Stabiliser	4.4

For product information contact 01621 745900
or email uk.customer@wernerco.com

DO MORE WITH
BOSS[®]