



Compact and Lightweight



Cutting capacity

Wood 135_{mm} Aluminum 20 mm

Steel 10 mm









with the cutting line easily.

(with disabling function)

Soft no-load speed mode

Reduces vibration and aligns blade



To turn on the tool, press the lock/ unlock button.

3,000

1,400 800

LED job light will turn on [standby mode]

For continuous operation






Variable speed triggre

ON loa



Bevel range



Work amount

on a single full battery charge

Efficiency of wood cutting

Battery: BL1860B Test material: MDF 24 x 300mm Max orbital action

Orbital setting lever



3 Orbital settings + Straight cutting

Variable speed control by dial



located on the rear side for easier operation

Toolless blade clamp



with a blade holder which allows for one-hand blade change

Accessories

Dust nozzle

Part No. 413F05-1





Guide rail



Front Dust nozzle Dust cover **└**Cover plate

Overall length

259_{mm}

Anti-splitering device

Part No. 192557-6



Guide rail adapter set Part No. 193517-1



Guide rule set Part No. 192732-4








Overall length	Part No.
1m	199140-0
1.4m	194368-5
1.9m	194925-9
3m	194367-7

18V LUTHUMHON	Fast Charging DC18RC	DC18SD
BL1815N 1.5Ah 196449-1	15 min	30 min
BL1820B 2.0Ah 197254-9	24 min	45 min
BL1830B 3.0Ah 197599-5	22 min	60 min
BL1850B 5.0Ah 197280-8	45 min	110 min
BL1860B 6.0Ah 197422-4	55 min	130 min



The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348 Phone: +65-6546-8700 Fax: +65-6546-8711 Email: msgproduct team@makita.com.sg

Website: www.makita.com.sg

Facebook: www.facebook.com/MakitaSG





