

**Accessories**



**For inflation**

**Nozzle 13 set**

Part No. 191X15-3  
Nozzle diameter: ø13mm  
(Same as the caliber of the machine)

- For blow-off works
- For inflating large play pools, etc.



**Nozzle 7 set**

Part No. 191X13-7  
Nozzle diameter: ø7.0mm

For filter cleaning



**Nozzle 3 set**

Part No. 191X11-1  
Nozzle diameter: ø3.0mm

For cleaning narrow spaces (can be used like an air spray can)



**Flexible nozzle complete set**

Part No. 191X21-8  
Nozzle diameter: ø6.0x800 (Hose)

For blowing dust away from OA equipment or narrow spaces where this machine cannot enter



**For inflation**

**Wide range nozzle set**

Part No. 191X19-5  
Nozzle diameter: ø6.0mm (each hole)

Blowing air over dirt and liquid on desktop and wide-open area.



**Pinch valve nozzle set**

Part No. 191X17-9  
Nozzle diameter: ø7.0mm

For inflating/deflating inner tubes and beach balls



**Long nozzle set**

Part No. 191X78-9  
Nozzle diameter: ø8.0mm

- For cleaning anchor holes
- For cleaning narrow spaces that are out of reach

Long nozzle F

Long nozzle R

- Long nozzle R can be used as a single item.
- It can also be used as an assembly with Nozzle 13.



**For deflation**

**Air vent hose complete set**

Part No. 191X23-4  
Nozzle diameter: 13mm (Same as the caliber of the machine)  
For inflating/deflating inner tubes and beach balls (Remove Dust cap complete from this machine and attach this hose.)



**Rubber attachment 20-30 set**

Part No. 191X25-0  
Nozzle diameter: 7.0mm

For deflation large play pools and inflatable beds etc.\*1



**Rubber attachment 65 set**

Part No. 191X27-6  
Nozzle diameter: ø65mm

For deflating futon (bedding) compression bag\*1



**For product protection**

**Filter C complete set**

Part No. 191X29-2  
For use of the machine in a dusty environment

(Remove Dust cap complete from this machine and attach this Filter.)



\*1 Used by attaching to Nozzle 13 and Air vent hose

**Charging Time**

**AS001G**

	Fast Charging DC40RA	DC40RC
**BL4020 2.0Ah 191L29-0	22 min	30 min
**BL4025 2.5Ah 191B36-3	28 min	38 min
**BL4040 4.0Ah 191B26-6	45 min	67 min
**BL4050F 5.0Ah 191L47-8	50 min	85 min
**BL4080F 8.0Ah 191X65-8	76 min	170 min

**DAS180**

	Fast Charging DC18RC	DC18SD
BL1815N 1.5Ah 196449-1	15 min	30 min
BL1820B 2.0Ah 197254-9	24 min	45 min
BL1830B 3.0Ah 197599-5	22 min	60 min
BL1850B 5.0Ah 197280-8	45 min	110 min
BL1860B 6.0Ah 197422-4	55 min	130 min

**Cordless Dust Blower**

**AS001G / DAS180**

Variable Speed	Air volume	0-1.1 m <sup>3</sup> /min
	Air velocity	0-200 m/s
Electronic 4-Speed	Air pressure	0-29.7 kPa
	Blowing force	Mode 1 / 2 / 3 / 4: 0-1.1 / 0-1.7 / 0-2.3 / 0-2.8 N
	Max sealed suction	10.3 kPa
Built-in Job Light	Continuous Use (min.)	AS001G: w/ BL4025, Mode 1 / 2 / 3 / 4: 50 / 25 / 17 / 13 DAS180: w/ BL1860B, Mode 1 / 2 / 3 / 4: 55 / 30 / 20 / 15
	Sound pressure level	79 dB(A)
	Vibration level	2.5 m/s <sup>2</sup> or less
	Dimensions (L x W x H)	AS001G: w/ BL4020 / BL4025: 180 x 94 x 300 mm (7-1/8 x 3-11/16 x 11-3/4") w/o Battery: 175 x 94 x 248 mm (6-7/8 x 3-11/16 x 9-3/4") DAS180: w/ BL1830B / BL1840B / BL1850B / BL1860B: 179 x 92 x 297 mm (7 x 3-5/8 x 11-3/4") w/o Battery: 173 x 92 x 247 mm (6-13/16 x 3-5/8 x 9-3/4")
	Net weight	AS001G: 1.5 - 2.3 kg (3.3 - 5.1 lbs.) DAS180: 1.2 - 1.7 kg (2.6 - 3.7 lbs.)

Standard Equipment : Nozzle, Pinch valve nozzle, Wide range nozzle, Flexible nozzle, Air vent hose, Rubber attachment, Filter, Belt clip, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

**Makita Singapore Pte Ltd**

7, Changi South Street 3, Singapore 486348  
Phone : +65-6546-8700 Fax : +65-6546-8711  
Email : msgproductteam@makita.com.sg  
Website : www.makita.com.sg  
Facebook : www.facebook.com/MakitaSG



MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE



**Cordless Dust Blower**  
**AS001G**  
**DAS180**



**Blowing**



**Inflating**



**Deflating**

**A wide range of applications**

Can be used for a wide range of applications by replacing the tip nozzle



AS001G



DAS180





**Nozzle 13 set**  
Part No. 191X15-3  
• For blow-off works  
• For inflating large play pools, etc.



**Nozzle 7 set**  
Part No. 191X13-7  
For filter cleaning



**Nozzle 3 set**  
Part No. 191X11-1  
For cleaning narrow spaces (can be used like an air spray can)



**Wide range nozzle set**  
Part No. 191X19-5  
Blowing air over dirt and liquid on desktop and wide-open area.



# A wide range of applications



**Flexible nozzle complete set**  
Part No. 191X21-8  
For blowing dust away from OA equipment or narrow spaces where this machine cannot enter



**Pinch valve nozzle set**  
Part No. 191X17-9  
For inflating/deflating inner tubes and beach balls



**Rubber attachment 20-30 set**  
Part No. 191X25-0  
For deflation large play pools and inflatable beds etc.\*1



**Rubber attachment 65 set**  
Part No. 191X27-6  
For deflating futon (bedding) compression bag\*1



\*1 Used by attaching to Nozzle 13 and Air vent hose

Max air velocity  
**200 m/s**  
[with Nozzle 7 / Mode 4]

Max air volume  
**1.1 m<sup>3</sup>/min**  
[without Nozzle / Mode 4]

**BL MOTOR**

Variable speed control by trigger



4 stage air volume



Hanging hole



**Filter**  
For preventing foreign matter from being sucked in



**One-touch nozzle replacement**  
Easy nozzle replacement without tool



**Air vent hose complete set**  
For inflating/deflating inner tubes and beach balls



\*Remove Dust cap complete from this machine and attach this hose.



**Filter C complete set**  
For use of the machine in a dusty environment



\*Remove Dust cap complete from this machine and attach this Filter.



## Cordless Dust Blower

**XGT**  
**40V<sup>Li-ion</sup> max**

**AS001G**

Max sealed suction  
**10.3 kPa**

Continuous run time  
Battery: BL4025

Mode	1	2	3	4
	50 min	25 min	17 min	13 min



**18V<sup>Li-ion</sup>**  
**LITHIUM-ION**

**DAS180**

Max sealed suction  
**10.3 kPa**

Continuous run time  
Battery: BL1860B

Mode	1	2	3	4
	55 min	30 min	20 min	15 min

