



Cordless Air Compressor AC001G



XGT
40V **Li-ION**
max



Low noise

68 dB(A)

Tank capacity

7.6 L

Max Pressure

0.93 MPa

Lightweight Battery: BL4020-BL4080F

11.6-12.8 kg



Surrounding environment-friendly machine with low noise level

Low noise
68 dB(A)

Rigid roll cage frame construction
minimizes the chance of damage to the motor and compression units.

Carrying handle
with rubberized grip designed for easy transportation



Air filter (air intake)



Oil-free pump design

Powered by 40Vmax XGT Li-Ion battery



BL MOTOR

High operating efficiency motor

One outlet (coupler)

Air tank capacity: 7.6L
Max air pressure in tank: 0.93MPa
The cut-in pressure is 0.72MPa

Charging Time

	Fast Charging DC40RA	DC40RC
**BL4020 2.0Ah 191L29-0	22 min	30 min
**BL4025 2.5Ah 191B36-3	28 min	38 min
**BL4040 4.0Ah 191B26-6	45 min	67 min
**BL4050F 5.0Ah 191L47-8	50 min	85 min
**BL4080F 8.0Ah 191X65-8	76 min	170 min

*1 Recommended battery

Cordless Air Compressor AC001G

Tank	7.6 L (2 gal)
Cut-In Pressure	0.72 MPa (105 PSI)
Cut-Out Pressure	0.93 MPa (135 PSI)
Number of Outlets	1
Performance	34.0 L/min
Noise Level	68 dB(A)
Dimensions (L x W x H)	302x434x382 mm (11-7/8" x 17-1/8" x 15")
Net weight	11.6 - 12.8 kg (25.6 - 28.2 lbs.)

Battery & Charger Sold Separately

The weight does not include battery cartridge
Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



f MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE