



Cordless Pruning Saw

DUC150 150 mm (6")
UC100D 100 mm (4")



photo: DUC150

photo: UC100D

Accessories

File holder set

4.0 mm (5/32")



Guide bar

For DUC150 : 1912F1-4
For UC100D : 1910W0-3



Chain oil

100mL
(country-specific)
Part no. 182229-1



Saw chain

For DUC150 : 1912E8-3
For UC100D : 1910V6-4



	DUC150	UC100D
Length	150 mm (6")	100 mm (4")
Gauge	1.1 mm (0.043")	

	DUC150	UC100D
Type	80TXL	
Number of links	32	26
Pitch	0.325"	
Gauge	1.1 mm (0.043")	

Holster set

Storage and carrying of the machine
For both 100mm/150mm models
Part no. 1913K4-9



Charging Time

Battery Model	12V ^{max} LITHIUM-ION		18V ^{max} LITHIUM-ION		
	DC10SB	DC10WD	DC18RC	DC18SD	
BL1016 1.5Ah 197393-5	22min	50min	15min	30min	
BL1021B 2.0Ah 197396-9	30min	70min	24min	45min	
BL1041B 4.0Ah 197406-2	60min	130min	45min	110min	
			BL1815N 1.5Ah 196449-1	15min	30min
			BL1820B 2.0Ah 197254-9	24min	45min
			BL1830B 3.0Ah 197599-5	22min	60min
			BL1850B 5.0Ah 197280-8	45min	110min
			BL1860B 6.0Ah 197422-4	55min	130min

Cordless Pruning Saw

DUC150 150 mm (6")

	DUC150	UC100D
Brake	Yes	Yes
Automatic Oiling	Yes	Yes
Saw chain	Type: 80TXL / Gauge: 1.1 mm (0.043") Pitch: 0.325" / Number of links: 32	Type: 80TXL / Gauge: 1.1 mm (0.043") Pitch: 0.325" / Number of links: 26
Guide bar length	150 mm (6")	100 mm (4")
Max cutting length	161 mm	111 mm
Chain speed	8.0 m/s (480 m/min) (1,570 FPM)	8.0 m/s (480 m/min) (1,570 FPM)
Chain oil tank volume	55 mL (1.9 USoz)	55 mL (1.9 USoz)
Vibration level Cutting wood:	4.8 m/s ²	4.8 m/s ²
Dimensions (L x W x H)	w/o Battery: 408 x 90 x 232 mm (16 x 3-1/2 x 9-1/8") w/ BL1815N / BL1820B: 445 x 90 x 245 mm (17-1/2 x 3-1/2 x 9-5/8") w/ BL1830B / BL1840B / BL1850B / BL1860B: 459 x 90 x 249 mm (18 x 3-1/2 x 9-3/4")	w/o Battery: 350 x 90 x 215 mm (13-3/4 x 3-1/2 x 8-1/2") w/ BL1016/BL1021B: 383 x 90 x 220 mm (15-1/8 x 3-1/2 x 8-5/8") w/ BL1041B: 398 x 90 x 226 mm (15-5/8 x 3-1/2 x 8-7/8")
Net weight	1.7-2.0 kg (3.7-4.4 lbs.)	1.5-1.6 kg (3.3-3.5 lbs.)

Standard Equipment : Saw chain, Guide bar, Guide bar case, Round file set (country-specific), Chain oil (country-specific), Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE



photo: DUC150



DUC150



Net weight*
1.7 - 2.0 kg



UC100D



Net weight*
1.5 - 1.6 kg



* EPTA-Procedure 01/2014





photo: DUC150



photo: DUC150



photo: UC100D

Lightweight yet easy-to-use

Movable guard

covers the upper side of guide bar, and opens gradually wider as saw chain cuts deeper in branch.

Lock-off lever accessible from both sides



Guide bar length
 DUC150: **150mm**
 UC100D: 100mm

Work amount	
Test conditions: Cut ø50 cedar rod under an optimal pressing load of 20N or less on cutting edge. Saw chain: 80TXL	
DUC150 210 pcs. Battery: BL1830B	UC100D 73 pcs. Battery: BL1021B

photo: DUC150

BL MOTOR

Compact and lightweight BL motor

XPT

eXtreme Protection Technology

Automatic chain lubrication

Oil tank cap Chain oil view window

minimizes the chance that saw chain will stall due to forgetting to supply chain oil.

New Tool-less change and tension adjustment of saw chain

- Simply loosen and re-tighten the lever to automatically adjust the tension of saw chain.
- This easy-to-operate large lever is designed to be pulled up and turned easily.