



Stroke		
Length	Per Minute	
22 mm	0 - 3,100 spm	





Powered by 18V LXT Li-lon battery **High power & low vibration**





High operating efficiency



Counter weight mechanism

Vibration Level Cutting boards 9.0 m/s²





with preglow and afterglow functions illuminates cutting area

Constant speed

control minimizes reduction in cutting speed under



Fixed type Shoe, pivoting shoe plate



One-touch tool-less blade clamp

Redesign of Blade clamp makes it easier to remove a blade.



eXtreme Protection Technology



Accessories

Wide hook (Tool hanger) Part No. 197224-8



Charging Time

18V	Fast Cyarging DC18RC	DC18SD
BL1815N 1.5Ah 196449-1	15 min	30 min
BL1820B 2.0Ah 197254-9	24 _{min}	45 min
BL1830B 3.0Ah 197599-5	22 min	60 min
BL1850B 5.0Ah 197280-8	45 min	110 min
BL1860B 6.0Ah 197422-4	55 min	130 min

Cordless Recipro Saw

DJR189

Variable Speed

(Brake

Constant Speed

Items of standard equipment and specification

■ Built-in Job Light

Length of stroke Strokes per minute (SPM) Capacity

Sound Pressure Level Sound Power Level Vibration Level

Dimensions (L x W x H)

Net weight

0 - 3,100 Wood: 255 mm (10"), Pipe: 130 mm (5-1/8") 88 dB(A) 99 dB(A) Cutting boards: 9.0 m/s²
Cutting wooden beams: 8.7 m/s²
w/BL1815N/BL1820B:
393 x 81 x 179 mm

(15-1/2 x 3-3/16 x 7") w/BL1830B/BL1840B/BL1850B/BL1860B: 410 x 81 x 182 mm (16-1/8 x 3-3/16 x 7-1/8") 2.2 - 2.5 kg (4.9 - 5.5 lbs.)

22 mm (7/8")

Standard Equipment: Recipro saw blades, Battery, Charger The weight may differ depending on the attachment(s), including the battery cartridge.
The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. may vary by country or area

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348 Phone: +65-6546-8700 Fax: +65-6546-8711 Email: msgproduct team@makita.com.sgWebsite: www.makita.com.sg

Facebook: www.facebook.com/MakitaSG











DOWNLOAD LEAFLET