

Accessories
Dust collection wheel guard

A: for offset diamond wheel
B: for diamond wheel



| Part No. | Size | Type |
|-----------|-------|------|
| *191F81-2 | 125mm | A |
| *191G06-2 | 125mm | B |

*Cannot be installed undetachable wheel cover models

Cutting wheel cover attachment for cutting work

Can be attached to the wheel cover for grinding with easy assembling.

| Part No. | Size |
|----------|-------|
| 199709-0 | 115mm |
| 199710-5 | 125mm |



Wheel cover

for cut-off wheel

| Part No. | Size |
|-----------|-------|
| *162555-4 | 100mm |
| *162556-2 | 115mm |
| *162557-0 | 125mm |



Vibration proof grip set

Part No. 194514-0



Dust cover attachment set

Part No. 199514-5



Angle Grinder
GA4050R / GA4550R / GA5050R



Photo: GA5050

Powerful 1,300 W Motor with Paddle Switch Trigger

Angle Grinder

GA4050R / GA4550R / GA5050R

260

| | GA4050R | GA4550R | GA5050R |
|-------------------|-----------------------------|--|--|
| Double Insulation | Anti-restart function model | | |
| Soft Start | Continuous rating input | 1,300W | 1,300W |
| Dust Collection | Wheel Diameter | 100 mm (4") | 115 mm (4-1/2") |
| | No Load Speed (RPM) | 11,000 | 11,000 |
| | Vibration Level | Surface Grinding: 6.5 m/s ² | Surface Grinding: 7.0 m/s ² |
| | (Normal side grip) | Disc Sanding: 2.5 m/s ² or less | Disc Sanding: 2.5 m/s ² |
| | Sound Pressure Level | 91 dB(A) | 91 dB(A) |
| | Sound Power Level | 102 dB(A) | 102 dB(A) |
| | Dimensions | 325x117x110 mm | 325x130x117 mm |
| | (L x W x H) | (12-3/4"x4-5/8"x4-5/16") | (12-3/4"x5-1/8"x4-5/8") |
| | Net weight | 2.3-2.6 kg (5.1-5.7 lbs.) | 2.4-2.8 kg (5.3-6.2 lbs.) |
| | Power supply cord | 2.5 m (8.2 ft.) | 2.5 m (8.2 ft.) |

Standard Equipment:
Depressed Center Wheel, Side Grip, Wheel Cover, Lock Nut Wrench

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd
7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



VISIT OUR WEBSITE

PRINTED IN SINGAPORE



Angle of side grip to gear housing: 110°


| | | |
|---------|---------|---------|
| 100mm | 115mm | 125mm |
| GA4050R | GA4550R | GA5050R |

**Soft start/
Anti-restart
function**

Easy-to-operate large paddle switch trigger
works properly wherever the user holds the barrel grip.



High durability
cutting and grinding, due to longer service life of motor, carbon brushes, etc.



Enhanced shaft locking mechanism

- Gear housing is redesigned to prevent breakage of the shaft locking mechanism.
- Large size lock pin cap allows for normal shaft locking operation even with a thick-gloved finger.



Machined bevel gears

Toolless wheel cover (Slide lever style)

allows for fast and easy angle adjustment and installation/removal of wheel cover.



Angle of side grip to gear housing

GA4050R / GA4550R / GA5050R



Anti-drop holders
allows to attach anti-drop strap, etc.



Easy-to-hold barrel grip

provides less hand fatigue and more control of the machine due to:

- Grip circumference smaller than 9564P series
- Ergonomic design



With soft start

Minimizes start-up shock and makes the tool start smoothly

With anti-restart function

Minimizes accidental start-up even if the tool is plugged to power source with the switch "ON".

Photo: GA5050

| Model No. | Wheel size | | | Angle of side grip to gear housing | Soft start | Anti-restart function |
|-----------|------------|---------|-------|------------------------------------|------------|-----------------------|
| | 100mm | 115mm | 125mm | | | |
| GA4050R | GA4550R | GA5050R | 110° | • | • | |