

Ardex Quicseal Malaysia Sdn. Bhd.

Chemwatch: 5565-33 Version No: 2.1

Safety Data Sheet according to CLASS requirements 2013

SECTION 1: Identification of the hazardous chemical and of the supplier

Product Identifier

QUICSEAL 103M – ACRYLFLEX			
Not Applicable			
Not Available			
Not Applicable			
Not Available			
N N			

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Liquid-applied waterproofing membrane. Use according to manufacturer's directions.

Details of the manufacturer or supplier of the safety data sheet

Registered company name	Ardex Quicseal Malaysia Sdn. Bhd.		
Address	No. 15, Jalan Desa Tropika 2/2 Taman Perindustrian Tropika Ulu Tiram, Johor 81800 Malaysia		
Telephone	607 8620 833		
Fax	+607 8620 793		
Website	Not Available		
Email	Not Available		

Emergency telephone number

Association / Organisation	Ardex Quicseal Malaysia Sdn. Bhd.	
Emergency telephone numbers	+607 8620 833	
Other emergency telephone numbers	Not Available	

SECTION 2 Hazards identification

Classification of the substance or mixture			
Classification ^[1]	Not Applicable		
Label elements			
Hazard pictogram(s)	Not Applicable		
Signal word	Not Applicable		
Hazard statement(s)			
Not Applicable			
Precautionary statement(s) Pre	evention		
Not Applicable			
Precautionary statement(s) Re Not Applicable	sponse		
Precautionary statement(s) Sto Not Applicable	brage		
Precautionary statement(s) Dis	posal		

Chemwatch Hazard Alert Code: 0

Issue Date: **13/10/2022** Print Date: **30/06/2023** L.GHS.MYS.EN.E

Not Applicable

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substances

See section below for composition of Mixtures

Mixtures

CAS No %[weight] Name		Name		
Not Available	100	Ingredients determined not to be hazardous		
Legend:	end: 1. Classified by Chemwatch; 2. Classification drawn from ICOP; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available			

SECTION 4 First aid measures

Description of first aid measures			
Eye Contact	 If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. 		
Skin Contact	If skin or hair contact occurs: Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. 		
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary. 		
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. 		

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

There is no restriction on the type of extinguisher which may be used.

• Use extinguishing media suitable for surrounding area

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.		
Advice for firefighters			
Fire Fighting	 Fight fire from a safe distance, with adequate cover. If safe, switch off electrical equipment until vapour fire hazard removed. Use water delivered as a fine spray to control fire and cool adjacent area. Avoid spraying water onto liquid pools. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. 		
Fire/Explosion Hazard	 Non combustible. Not considered a significant fire risk, however containers may burn. 		

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety goggles. Trowel up/scrape up. Place spilled material in clean, dry, sealed container. Flush spill area with water. 		
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Control personal contact with the substance, by using protective equipment. Prevent spillage from entering drains, sewers or water courses. Recover product wherever possible. Put residues in labelled containers for disposal. If contamination of drains or waterways occurs, advise emergency services. 		

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

recautions for safe handling	
Safe handling	 Limit all unnecessary personal contact. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container	 Polyethylene or polypropylene container. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks. 	
Storage incompatibility Avoid contamination of water, foodstuffs, feed or seed. None known None known		

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-1 TEEL-2		TEEL-3	
QUICSEAL 103M – ACRYLFLEX	Not Available	Not Available		Not Available	
Ingredient	Original IDLH		Revised IDLH		
QUICSEAL 103M – ACRYLFLEX	Not Available	Not Available		Not Available	

MATERIAL DATA

Exposure controls

be highly effective in protecting workers and will typically The basic types of engineering controls are: Process controls which involve changing the way a job ac Enclosure and/or isolation of emission source which keep "adds" and "removes" air in the work environment. Ventila ventilation system must match the particular process and Employers may need to use multiple types of controls to p General exhaust is adequate under normal operating con essential to obtain adequate protection. Provide adequate		a selected hazard "physically" away from the worker and ven ion can remove or dilute an air contaminant if designed proper chemical or contaminant in use.	of protection. tilation that strategica ly. The design of a irator. Correct fit is nants generated in th
	Type of Contaminant:		
Annronriate engineering	Type of containing the		Air Speed:
Appropriate engineering controls	solvent, vapours, degreasing etc., evaporating from tank	(in still air)	Air Speed: 0.25-0.5 m/s (50-100 f/min)
	solvent, vapours, degreasing etc., evaporating from tank	ntainer filling, low speed conveyer transfers, welding, spray	0.25-0.5 m/s (50-100 f/min)
	solvent, vapours, degreasing etc., evaporating from tank aerosols, fumes from pouring operations, intermittent co drift, plating acid fumes, pickling (released at low velocity	ntainer filling, low speed conveyer transfers, welding, spray	0.25-0.5 m/s (50-100 f/min) 0.5-1 m/s (100-20 f/min.)
	solvent, vapours, degreasing etc., evaporating from tank aerosols, fumes from pouring operations, intermittent co drift, plating acid fumes, pickling (released at low velocity direct spray, spray painting in shallow booths, drum filling generation into zone of rapid air motion)	ntainer filling, low speed conveyer transfers, welding, spray into zone of active generation)	0.25-0.5 m/s (50-100 f/min) 0.5-1 m/s (100-20 f/min.) 1-2.5 m/s (200-50
	solvent, vapours, degreasing etc., evaporating from tank aerosols, fumes from pouring operations, intermittent co drift, plating acid fumes, pickling (released at low velocit) direct spray, spray painting in shallow booths, drum filling generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, high speed wheel g	ntainer filling, low speed conveyer transfers, welding, spray y into zone of active generation) g, conveyer loading, crusher dusts, gas discharge (active	0.25-0.5 m/s (50-100 f/min) 0.5-1 m/s (100-20 f/min.) 1-2.5 m/s (200-50 f/min) 2.5-10 m/s

	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	
	2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity	
	3: Intermittent, low production.	3: High production, heavy use	
	4: Large hood or large air mass in motion 4: Small hood - local control only Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.		
Individual protection measures, such as personal protective equipment			
Eye and face protection	 Safety glasses with side shields Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59]. 		
Skin protection	See Hand protection below		
Hands/feet protection	Wear general protective gloves, eg. light weight rubber gloves.		
Body protection	See Other protection below		
Other protection	No special equipment needed when handling small quantities. OTHERWISE: Overalls. Barrier cream. Eyewash unit.		

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Coloured thixotropic liquid, miscible in water. Coloured		
			1
Physical state	Free-flowing Paste	Relative density (Water = 1)	1.30
Odour	Characteristic	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	800-1250
Initial boiling point and boiling range (°C)	100	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	e section 7	
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.	
Possibility of hazardous reactions	See section 7	
Conditions to avoid	See section 7	
Incompatible materials	See section 7	
Hazardous decomposition products	See section 5	

SECTION 11 Toxicological information

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.			
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.			
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal			
Eye	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).			
Chronic		ct is not thought to produce chronic effects a by all routes should be minimised as a matte		th (as classified by EC Directives using animal
QUICSEAL 103M -	ΤΟΧΙΟΙΤΥ	IR	RITATION	
ACRYLFLEX	Not Available	No	ot Available	
Legend:		CHA Registered Substances - Acute toxicity ECS - Register of Toxic Effect of chemical S		ined from manufacturer's SDS. Unless otherwise
•	×	•		×
Acute Toxicity Skin Irritation/Corrosion	x		inogenicity productivity	×
Serious Eye Damage/Irritation	×	STOT - Single		×
Respiratory or Skin sensitisation	×	STOT - Repeated	d Exposure	×

Data either not available or accessification
 Data available to make classification

SECTION 12 Ecological information

Toxicity

	Endpoint	Test Duration (hr)	Species	Value	Source
QUICSEAL 103M – ACRYLFLEX	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Jap - Bioconcentration Data 8. Vendor Data		,		

DO NOT discharge into sewer or waterways.

Persistence and degradability

. e.e.e.e.ee and degrad					
Ingredient	Persistence: Water/Soil	Persistence: Air			
	No Data available for all ingredients	No Data available for all ingredients			
Bioaccumulative poten	tial				
Ingredient	Bioaccumulation	Bioaccumulation			
	No Data available for all ingredients				
Mobility in soil					
Ingredient	Mobility				
	No Data available for all ingredients				

SECTION 13: Disposal information

Waste treatment methods		
Product / Packaging disposal	 Recycle wherever possible or consult manufacturer for recycling options. Consult State Land Waste Management Authority for disposal. Bury residue in an authorised landfill. Recycle containers if possible, or dispose of in an authorised landfill. 	

SECTION 14 Transport information

Labels Required			
Marine Pollutant	NO		
HAZCHEM	Not Applicable		
and transport (UN): NOT REG	SULATED FOR TRANSPORT OF DANGEROUS GOODS		
Air transport (ICAO-IATA / DGF	R): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS		
sea transport (IMDG-Code / G0	GVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS		
Fransport in bulk according to Not Applicable	Annex II of MARPOL and the IBC code		
Fransport in bulk in accordance	e with MARPOL Annex V and the IMSBC Code		
Product name	Group		
Fransport in bulk in accordanc	e with the IGC Code		
Product name	Ship Type		
SECTION 15 Regulatory info	ormation		
afety, health and environmen	tal regulations / legislation specific for the substance or mixture		
This safety data sheet is in complia	ance with the Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013 (CLASS)		
lational Inventory Status			
National Inventory	Status		
Australia - AIIC / Australia	Not Available		

National Inventory	olados
Australia - AIIC / Australia Non-Industrial Use	Not Available
Canada - DSL	Not Available
Canada - NDSL	Not Available
China - IECSC	Not Available
Europe - EINEC / ELINCS / NLP	Not Available
Japan - ENCS	Not Available
Korea - KECI	Not Available
New Zealand - NZIoC	Not Available
Philippines - PICCS	Not Available
USA - TSCA	Not Available
Taiwan - TCSI	Not Available
Mexico - INSQ	Not Available
Vietnam - NCI	Not Available
Russia - FBEPH	Not Available
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	13/10/2022
Initial Date	13/10/2022

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC - TWA: Permissible Concentration-Time Weighted Average PC - STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit, IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substances Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

