

COLD WATER – FOUR WHEELS

The small quadro-Series



Integrated water tank

Prevents damage to the high-pressure pump caused by a lack of water

Integrated Hose drum

Practical design and features a longer length high-pressure hose complete with folding cranklength high-pressure hose complete with folding crank

Pressure regulation

Fully adjustable control allows operating pressures to be set to suit any task

Total-stop system

Auto-shutdown feature improves seal life-span and reduces power consumption

Roto-Mold-Chassis

Virtually indestructible

Cleaning Agent Intake

Injector system for dispensing of cleaning agents

Figures: quadro 11/140 TST



		quadro 11/140 TST	quadro 9/170 TST	quadro 12/150 TST
Technical specifications				
Operating pressure adjustable	bar / MPa	30-140 / 3-14	30-170 / 3-17	30-150 / 3-15
Max. admissible overpressure	bar / MPa	155 / 15.5	190 / 19	165 / 16.5
Connected load	V / ~ / Hz / A	230 / 1 / 50 / 14	230 / 1 / 50 / 14	400 / 3 / 50 / 6.8
Motor speed	Rpm	1400	1400	1400
Water output	l/min l/h	11 660	9 540	12 720
Power intake / Power output	kW kW	3.3 2.4	3.3 2.4	3.5 2.8
Volume water tank	l	7	7	7
Power supply cable	m	5	5	7.5
Dimensions L x W x H	mm	590 / 360 / 850	590 / 360 / 850	590 / 360 / 850
Weight	kg	46	46	46
Cleaning Agent Intake		●	●	●
Equipment				
Hose drum		●	●	●
Steel braided high-pressure hose	m	15	15	15
Trigger gun with safety catch	Model	M2000	M2000	M2000
Dirtkiller lance	Nozzle size	● 045	○ 03	● 045
Stainless steel lance with flat jet nozzle	Nozzle size	● M20045	○ M2003	● M20045
Ord.no.		404411	404431	404421



For detailed technical information, see page 78