



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product

Smoke Detector Test Spray
Code-Nr. 116402

1.2. Relevant identified uses of the substance or mixture and uses advised against Recommended intended purpose(s)

Technical Aerosols

1.3. Details of the supplier of the safety data sheet

Distributor

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone +49(0)251 / 9322 - 0
Fax +49(0)251 / 9322 - 244
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Aerosol 1	H222, H229	
Eye Irrit. 2	H319	
STOT SE 3	H336	

Hazard Statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS07

Signal word

Danger

Hazard Statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary Statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501	Dispose of contents/container to hazardous or special waste collection point.

2.3. Other hazards

Product has an anesthetic effect.

Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/ information on ingredients**3.1. Substances**

not applicable

3.2. Mixtures**Description**

Mixture of active ingredients with propellant

**Smoke Detector Test Spray****Hazardous ingredients**

CAS No	EC No	Name	[%]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
67-63-0	200-661-7	propan-2-ol	10-19,99	Flam. Liq. 2, H225 / Eye Irrit. 2, H319 / STOT SE 3, H336
74-98-6	200-827-9	propane	10 - 20	Flam. Gas 1, H220 / Press. Gas
75-28-5	200-857-2	isobutane	10 - 20	Flam. Gas 1, H220 / Press. Gas
106-97-8	203-448-7	butane	50-70	Flam. Gas 1, H220 / Press. Gas

REACH

CAS No	Name	REACH registration number
67-63-0	propan-2-ol	01-2119457558-25
74-98-6	propane	01-2119486944-21
75-28-5	isobutane	01-2119485395-27
106-97-8	butane	01-2119474691-32

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinsing with plenty of lukewarm water carefully and seek for medical treatment.

In case of ingestion

Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam

Dry powder

Carbon dioxide

Water spray jet

5.2. Special hazards arising from the substance or mixture

Danger of bursting

In case of fire formation of dangerous gases possible.

5.3. Advice for firefighters**Special protective equipment for fire-fighters**

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.



Additional information

Cool endangered containers with water spray jet.

Collect contaminated firefighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Allow to vaporise.

Additional Information

Sort out leaky cans and dispose according to regulations.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

! SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Do not inhale gases/vapours/aerosols.

Ensure sufficient ventilation.

Hygiene measures

At work do not eat, drink and smoke.

Wash hands before breaks and after work.

! Advice on protection against fire and explosion

Do not spray on a naked flame or any incandescent material.

Pressurized container.

Do not pierce or burn even after use.

Protect from heat and sunlight.

Vapours can form an explosive mixture with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

! Further information on storage conditions

Protect from heat and direct solar radiation.

Keep container dry and store at cool and aired place.

Storage temperature may not exceed 40°C (=104°F).

**Smoke Detector Test Spray****7.3. Specific end use(s)****Recommendation(s) for intended use**

See section 1.2

! SECTION 8: Exposure controls/personal protection**8.1. Control parameters****! Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
106-97-8	Butane	8 hours	1450	600	EH40/2005
		Short-term	1810	750	
67-63-0	propan-2-ol	8 hours	999	400	EH40/2005
		Short-term	1250	500	
75-28-5	iso-Butan (CH)	MAK, 8 hours	7600	3200	ZNS
		Short-term	1900	800	

DNEL-/PNEC-values**DNEL worker**

CAS No	Substance name	Value	Code	Remark
67-63-0	propan-2-ol	888 mg/kg bw/day	DNEL long-term dermal (systemic)	
		500 mg/m3	DNEL long-term inhalative (systemic)	

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls**Respiratory protection**

In case of insufficient ventilation or long-term effect use breathing apparatus.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min; 60min.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

! SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

aerosol

Colour

light yellow

Odour

characteristic

Odour threshold

**Smoke Detector Test Spray**

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	not applicable				
Melting point / Freezing point	not determined				
Flash point	not applicable				Aerosol
Vapourisation rate	not determined				
Flammable (solid)	not applicable				
Flammability (gas)	not determined				
Ignition temperature	365 °C				
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	1,5 %				
Upper explosion limit	12 %				
Vapour pressure	4400 hPa	20 °C			
Relative density	0,59 g/cm3	20 °C			
Vapour density	not determined				
Solubility in water					miscible
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not determined				
Viscosity kinematic	not determined				
Solvent content	99,5 %				

Oxidising properties

No information available.

Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .



9.2. Other information
No information available.

! SECTION 10: Stability and reactivity

10.1. Reactivity
No information available.

10.2. Chemical stability
The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions
No hazardous reactions known.

10.4. Conditions to avoid
Keep away from heat.
Formation of explosive gas/air mixtures.

10.5. Incompatible materials
No information available.

10.6. Hazardous decomposition products

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
Skin irritation	non-irritant			
Eye irritation	irritant			
Skin sensitization	non-sensitizing			

Additional information
The product is to be handled with the caution usual with chemicals.
Other hazardous properties may not be excluded.

! SECTION 12: Ecological information

12.1. Toxicity
No information available.

12.2. Persistence and degradability
No information available.

12.3. Bioaccumulative potential
No information available.

12.4. Mobility in soil



No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

! General regulation

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No.

15 01 04
15 01 10*

Name of waste

metallic packaging
packaging containing residues of or contaminated by hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Totally emptied packaging may be treated as household waste.

Recommended cleansing agent

Water

General information

For proper waste disposal a complete emptying of the tin is necessary.

! SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1950	1950	1950
14.2. UN proper shipping name	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)	2.1	2.1	2.1
14.4. Packing group	-	-	-
14.5. Environmental hazards	No	No	No

14.6. Special precautions for user

Caution: Gases

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 2.1

tunnel restriction code D

Classification code 5F



! Transport/further information
Marine pollutant: NO

! SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

VOC content	99,5 %
VOC value	589 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.
For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.
The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.
Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.6

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.