

TECHNICAL DATA SHEET FOR

NIPPON ROAD LINE PAINT

DESCRIPTION	:	It is tough, fast-drying and weather-durable coat formulated to withstand wear for road and floor marking
TYPE	:	Modified chlorinated rubber resin with thermoplastic property
COLOUR	:	White, Yellow (537 of BS 381C), Red and Black
FINISH	:	Matt
USES	:	For coating on <ul style="list-style-type: none"> • Concrete Floor • Asphalt • Plastered Wall
FEATURES	:	<ul style="list-style-type: none"> • Excellent eye visibility • Hard and abrasive resistant • Very fast drying • Weather resistant

APPLICATION DATA

METHOD	:	Roller, brush and air and airless spray												
THEORETICAL COVERAGE	:	10 m ² / litre (based on 40 microns DFT per coat)												
DILUTION	:	Use Nippon Road Line Paint Reducer <table> <tr> <td>Brush</td> <td>-</td> <td>10% max</td> </tr> <tr> <td>Roller</td> <td>-</td> <td>10% max</td> </tr> <tr> <td>Air Spray</td> <td>-</td> <td>10%-20%</td> </tr> <tr> <td>Airless Spray</td> <td>-</td> <td>0%-5%</td> </tr> </table>	Brush	-	10% max	Roller	-	10% max	Air Spray	-	10%-20%	Airless Spray	-	0%-5%
Brush	-	10% max												
Roller	-	10% max												
Air Spray	-	10%-20%												
Airless Spray	-	0%-5%												
SURFACE PREPARATION	:	The surface must be clean, dry and free from grease /oil and any other foreign matter.												

Painting System

Recommended two coats with minimum dry film thickness of 40 microns each for optimum performance.

SPRAY APPLICATION	:		<u>Air</u>	<u>Airless</u>
		Delivery Pressure(kg/cm ²)	3 - 4	140 - 170
		Tip size 60° angle	1.3mm	0.017"
		Dilution	10-20%	0-5%

NIPPON ROAD LINE PAINT

- DRYING TIME** : Touch Dry - 5 mins at 30° C
- OVERCOATING TIME** : 1 hour in normal conditions
- CLEANING** : All equipment should be cleaned with NIPPON ROAD LINE PAINT REDUCER immediately after use.

GENERAL INFORMATION

- CONFORMITY** : Nippon Road Line Paint (White, Yellow & Red) is certified under TÜV SÜD PSB Product Listing Scheme to SS 221:2002
- SOLID CONTENT** : 62 ± 2% by weight (based on white)
- SPECIFIC GRAVITY** : 1.33 ± 0.03 kg/litre (based on white)
- FLASH POINT** : 7 °C (for White, Yellow & Red)
23 °C (for Black)
- PACKING** : 5 litres
- STORAGE** : Store in a tightly sealed container in a cool and dry place
- SHELF LIFE** : Up to 24 months when stored in a tightly sealed container
- PRECAUTION** : Contain volatile solvents, keep away from naked flame.
Avoid direct contact with skin. Use appropriate protection equipment.
Refer to the product Safety Data Sheet for more information.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

- Enquiries / Contact Details** : **Customer Service**
6265 5355 (Main Line)
6264 1603 (Fax)
www.nipponpaint.com.sg