



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Zinc Spray (GB)
Code-Nr. 110000

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)
Technical Aerosols

1.3. Details of the supplier of the safety data sheet

Manufacturer/distributor WEICON GmbH & Co. KG
Königsberger Straße 255, DE-48157 Münster
Postbox 84 60, DE-48045 Münster
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244
E-Mail : info@weicon.de
Internet : www.weicon.de

Advice Abteilung Angebote, Verkauf, Export
Phone ++49(0)251 / 9322 - 0
E-mail (competent person):
info@weicon.de

1.4. Emergency telephone number

Emergency advice Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning)
Phone ++49(0)228-19 240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to 67/548/EEC or 1999/45/EC

F+; R12
N; R50/53

R-phrases

12 Extremely flammable.
50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Labelling according to 1999/45/EC

Remarks for labelling

The product is classified and labelled in accordance with EC directives/German regulations on dangerous substances.

F+ Extremely flammable
N Dangerous for the environment

R-phrases

12 Extremely flammable.
50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-phrases

23 Do not breathe spray.
29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
51 Use only in well-ventilated areas.
61 Avoid release to the environment. Refer to special instructions/safety data sheets.

**Zinc Spray (GB)****Special rules for supplemental label elements for certain mixtures**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Without sufficient ventilation the formation of explosive vapour/air mixtures cannot be excluded. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

2.3. Other hazards**Information pertaining to special dangers for human and environment**

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

SECTION 3: Composition/ information on ingredients**3.1. Substances**

not applicable

3.2. Mixtures**Description**

Zinc spray based on synthetic resin binder, solvent and pigments.

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to 67/548/EEC
67-64-1	200-662-2	acetone	2,5 - 10	F R11; Xi R36; R66; R67
7429-90-5	231-072-3	aluminium powder (stabilised)	<= 2,5	F R11-15
7440-66-6	231-175-3	zinc powder - zinc dust (stabilized)	10 - 24	N R50-53
115-10-6	204-065-8	dimethylether	50 - 99	F+ R12
123-86-4	204-658-1	n-butyl acetate	2,5 - 10	R10; R66; R67
141-78-6	205-500-4	ethyl-acetate	2,5 - 10	F R11; Xi R36; R66; R67
1330-20-7	215-535-7	xylene	2,5 - 10	R10; Xn R20/21; Xi R38
3006-13-1	221-108-6	Dodecylethyldimethylammonium ethyl sulphate	<= 2,5	Xn R22; N R50/53

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
67-64-1	200-662-2	acetone	2,5 - 10	Flam. Liq. 2, H225 / Eye Irrit. 2, H319 / STOT SE 3, H336
7429-90-5	231-072-3	aluminium powder (stabilised)	<= 2,5	Water-react. 2, H261 / Flam. Sol. 1, H228
7440-66-6	231-175-3	zinc powder - zinc dust (stabilized)	10 - 24	Aquatic Acute 1, H400 / Aquatic Chronic 1, H410
115-10-6	204-065-8	dimethylether	50 - 99	Flam. Gas 1, H220 / Press. Gas
123-86-4	204-658-1	n-butyl acetate	2,5 - 10	Flam. Liq. 3, H226 / STOT SE 3, H336
141-78-6	205-500-4	ethyl-acetate	2,5 - 10	Flam. Liq. 2, H225 / Eye Irrit. 2, H319 / STOT SE 3, H336
1330-20-7	215-535-7	xylene	2,5 - 10	Flam. Liq. 3, H226 / Acute Tox. 4, H332 / Acute Tox. 4, H312 / Skin Irrit. 2, H315
3006-13-1	221-108-6	Dodecylethyldimethylammonium ethyl sulphate	<= 2,5	Acute Tox. 4, H302 / Aquatic Acute 1, H400 / Aquatic Chronic 1, H410

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.



In case of skin contact

In case of contact with skin wash off with soap and water.
Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Do not induce vomiting.
Medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Dry powder
Carbon dioxide
sand

Unsuitable extinguishing media

water

5.2. Special hazards arising from the substance or mixture

Danger of bursting
Fire gas of organic material has to be classed invariably as respiratory poison.

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.
Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Additional information

Vapours are heavier than air and will spread on the ground.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.
Use personal protective clothing.
Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains or bodies of water..

6.3. Methods and material for containment and cleaning up

Take up with absorbent material.
After taking up the material dispose according to regulation.

6.4. Reference to other sections

No information available.



SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink, smoke or take drugs.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Pressurized container.

Do not pierce or burn even after use.

Vapours can form an explosive mixture with air.

Avoid effect of heat.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Advice on storage compatibility

Do not store with combustible materials.

Further information on storage conditions

Protect from direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

Store container at cool and aired place.

Keep in a cool place.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m ³]	[ppm]	Remark
67-64-1	Acetone	8 hours	1210	500	EH40/2005
		Short-term	3620	1500	
7429-90-5	Aluminium metal: inhalable dust	8 hours	10		EH40/2005
7429-90-5	Aluminium metal: respirable dust	8 hours	4		EH40/2005
115-10-6	Dimethyl ether	8 hours	766	400	EH40/2005
		Short-term	958	500	
141-78-6	Ethyl acetate	8 hours		200	EH40/2005
		Short-term		400	
1330-20-7	Xylene, o-, m-, p- or mixed isomers	8 hours	220	50	EH40/2005
		Short-term	441	100	

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m ³]	[ppm]	Remark
115-10-6	dimethylether	8 hours	1920	1000	
1330-20-7	xylene, mixed isomers, pure	8 hours	221	50	skin
		Short-term	442	100	
67-64-1	acetone	8 hours	1210	500	

**8.2. Exposure controls****Respiratory protection**

If ventilation insufficient, wear respiratory protection.

Short term: filter apparatus, Filter A/P2

Hand protection

When using chemical substances protective gloves against chemicals must be worn with the CE-label including the four control digits.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves. Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

Eye protection

safety goggles

Skin protection

protective clothing

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Form**

aerosol

Colour

silver-grey

Odour

solvent-like

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
boiling point	-24 °C				
Flash point	ca. -42 °C				
Ignition temperature	365 °C				
Lower explosion limit	1,1 Vol-%				
Upper explosion limit	18,6 Vol-%				
Vapour pressure	5200 hPa	20 °C			
Relative density	not determined				
Solubility in water					insoluble

Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

9.2. Other information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No information available.

**10.4. Conditions to avoid**

Keep away from heat.

Formation of explosive gas/air mixtures.

Hydrogen formation in heat under influence of acids and alkalies.

10.5. Incompatible materials**Materials to avoid**

Reactions with acids, alkalies and oxidising agents.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Hydrogen

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity/Irritability/Sensitization**

	Value/Validation	Species	Method	Remark
Irritability skin	non-irritant			
Irritability eye	non-irritant			
Skin sensitization	non-sensitizing			

Experiences made from practice

Vapours may cause dizziness, headaches and tiredness

Inhalation causes narcotic effect/intoxication.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

Labelling in compliance with the assessment procedure specified in the EC guidelines 1999/45/EC.

SECTION 12: Ecological information**12.1. Toxicity**

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6. Other adverse effects**General regulation**

Even in the event of low quantities penetration into the underground drinking water is contaminated.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.



SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No.

15 01 10*

Name of waste

packaging containing residues of or contaminated by dangerous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

There are no harmonised regulations on the disposal of chemicals in the member states of the EU. In Germany, the Recycling and Waste Management Act 8 KrW-/AbfG) stipulates recycling as a requirement.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

For proper waste disposal a complete emptying of the tin is necessary.

SECTION 14: Transport information

Land and inland navigation transport ADR/RID

UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS, Classification code: 5F
transport in "limited quantities" according to 3.4 ADR is possible

Marine transport IMDG

UN 1950 AEROSOLS (ZINC POWDER), 2.1

MARINE POLLUTANT: Yes

Transport as limited quantities according to 3.4 IMDG Code is possible.

Air transport ICAO/IATA-DGR

UN 1950 Aerosols, flammable, 2.1

ENVIRONMENTALLY HAZARDOUS: Yes

Transport/further information

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)

Special precautions for user

No information available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard**Remark**

Daten separat anfragen / Request data separately.

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Wording of the R/H-phrases specified in chapter 3 (not the classification of the mixture!)

R 10 Flammable.

R 11 Highly flammable.

R 12 Extremely flammable.



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed

17.05.2013

revision

06.05.2013 (GB) Version 8.0

Zinc Spray (GB)

- R 15 Contact with water liberates extremely flammable gases.
- R 20/21 Harmful by inhalation and in contact with skin.
- R 22 Harmful if swallowed.
- R 36 Irritating to eyes.
- R 38 Irritating to skin.
- R 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R 66 Repeated exposure may cause skin dryness or cracking.
- R 67 Vapours may cause drowsiness and dizziness.

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H261 In contact with water releases flammable gas.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.