



! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Multi-Foam
Code-Nr. 112000

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

Technical Aerosols

1.3. Details of the supplier of the safety data sheet

Distributor

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone +49(0)251 / 9322 - 0, Fax +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone +49(0)251 / 9322 - 0
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Aerosol 1	H222, H229	
Eye Irrit. 2	H319	

Hazard Statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]


GHS02



GHS07

Signal word

Danger

Hazard Statements

H222 Extremely flammable aerosol.
 H229 Pressurised container: May burst if heated.
 H319 Causes serious eye irritation.

Precautionary Statements

P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264 Wash hands thoroughly after handling.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337 + P313 If eye irritation persists: Get medical advice/attention.
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/container to hazardous or special waste collection point.

2.3. Other hazards
Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/ information on ingredients
3.1. Substances

not applicable

3.2. Mixtures
Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
67-63-0	200-661-7	propan-2-ol	10 - 15	Flam. Liq. 2, H225 / Eye Irrit. 2, H319 / STOT SE 3, H336
75-28-5	200-857-2	isobutane	2,5 - 10	Flam. Gas 1, H220 / Press. Gas
74-98-6	200-827-9	propane	2,5 - 10	Flam. Gas 1, H220 / Press. Gas
1336-21-6	215-647-6	Ammoniak 2,5%	0,1 < 0,5	Skin Corr. 1B, H314 / Aquatic Acute 1, H400

REACH

CAS No	Name	REACH registration number
--------	------	---------------------------

**REACH (continued)**

CAS No	Name	REACH registration number
67-63-0	propan-2-ol	01-2119457558-25
74-98-6	propane	01-2119486944-21

Labelling for contents according to regulation (EC) No 648/2004, annex VII

less than 5 % anionic surfactants, scents (CITRAL, D-LIMONENE)

5 % or over but less than 15 % aliphatic hydrocarbons

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off immediately with plenty of water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

In case of ingestion

Do not induce vomiting.

Medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam

Dry powder

Carbon dioxide

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

May lead to formation of explosive/easily ignitable vapour air mixtures.

Danger of bursting

In case of fire formation of dangerous gases possible.

Carbon monoxide (CO)

Carbon dioxide (CO₂)**5.3. Advice for firefighters****Special protective equipment for fire-fighters**

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.



Additional information

Cool endangered containers with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

Additional Information

Sort out leaky cans and dispose according to regulations.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink and smoke.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Pressurized container.

Do not pierce or burn even after use.

Protect from heat and sunlight.

Vapours can form an explosive mixture with air.

Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Further information on storage conditions

Protect from direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

Store container at cool and aired place.

7.3. Specific end use(s)
Recommendation(s) for intended use

See section 1.2

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
106-97-8	Butane	8 hours	1450	600	EH40/2005
		Short-term	1810	750	
67-63-0	propan-2-ol	8 hours	999	400	EH40/2005
		Short-term	1250	500	

DNEL-/PNEC-values
DNEL worker

CAS No	Substance name	Value	Code	Remark
67-63-0	propan-2-ol	888 mg/kg bw/day	DNEL long-term dermal (systemic)	
		500 mg/m3	DNEL long-term inhalative (systemic)	

8.2. Exposure controls
Respiratory protection

Breathing apparatus in the event of aerosol or mist formation.

Short term: filter apparatus, filter AX

Hand protection

When using chemical substances protective gloves against chemicals must be worn with the CE-label including the four control digits.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties
Appearance

aerosol

Colour

colourless

Odour

fruity

Odour threshold

**Multi-Foam**

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	not applicable				
melting point	not determined				
Flash point	not applicable				Aerosol
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	> 200 °C				
Self ignition temperature	not determined				
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	ca. 5 bar	20 °C			
Relative density	0,9 g/cm ³	20 °C			
Vapour density	not determined				
Solubility in water					miscible
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity	not determined				
Solvent content	23,1 %				

Oxidising properties

No information available.

Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

Keep away from heat.

Formation of inflammable vapour-air mixtures.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Aldehydes

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	5045 mg/kg	rat		Information concerns to main component.
LD50 acute dermal	12800 mg/kg	rabbit		Informations concern to main component.
LC50 acute inhalation	20 mg/l (4 h)	rat		Propane
Skin irritation	non-irritant			
Eye irritation	irritant			
Skin sensitization	non-sensitizing			

Experiences made from practice

Inhalation causes narcotic effect/intoxication.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.



SECTION 12: Ecological information**12.1. Toxicity**

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects**General regulation**

Ecological data are not available.

Product is not allowed to be discharged into aquatic environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Waste code No.**

15 01 04

16 05 04*

Name of waste

metallic packaging

gases in pressure containers (including halons) containing hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

For proper waste disposal a complete emptying of the tin is necessary.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1950	1950	1950
14.2. UN proper shipping name	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)	2.1	2.1	2.1
14.4. Packing group	-	-	-
14.5. Environmental hazards	No	No	No



14.6. Special precautions for user

Caution: Gases

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 2.1

tunnel restriction code D

Classification code 5F

transport in "limited quantities" according to 3.4 ADR is possible

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

VOC content 23,03 %

VOC value 208,4 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.4

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.