



TAPMATIC TRICUT

CUTTING FLUID



FEATURES

- Excellent for stainless steel and other hard to machine metals
- Provides smooth, accurate cutting action
- Flows directly to the cutting edge
- Extends tool life
- Improves surface finish
- Allows increased removal rates
- Reduces friction
- Suitable for high and low speed applications
- Not recommended for aluminum

PACKAGES

Net Fill
16 fl.oz. (0.473 l)
1 gal. (3.78 l)

Part No.
05316
05328

APPLICATIONS

- Boring
- Broaching
- Drawing
- Drilling
- Engraving
- Facing
- Milling
- Reaming
- Sawing
- Stamping
- Tapping
- Threading
- Turning



PROPERTIES

Color:
Dark brown/black

Odor:
Mild pine

Flash Point :
> 302°F (150°C) PMCC

Boiling Point:
302°F (150°C)

Specific Gravity (Water=1):
1.1 – 1.2

Partition Coefficient (octanol/water):
< 1

Volatiles:
< 0%

Viscosity:
130 - 160 cPs

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2010 LPS Laboratories • LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2141 • Rev. 1/2010