



SAFETY DATA SHEET

1. Identification

| | |
|---|--|
| Product identifier | LPS® U-10 |
| Other means of identification | |
| Part Number | 06220 |
| Recommended use | A spray brake cleaner designed to remove oil, grease, brake fluid, brake pad material or dirt from motor vehicle brake mechanisms. |
| Recommended restrictions | None known. |
| Manufacturer/Importer/Supplier/Distributor information | |
| Manufacturer | |
| Manufacturer | |
| Company name | LPS Laboratories, a division of Illinois Tool Works, Inc. |
| Address | 4647 Hugh Howell Rd. Tucker, GA 30084 (U.S.A.) |
| Country | (U.S.A.) |
| In Case of Emergency | Tel: +1 770-243-8800 1-800-424-9300 (inside U.S.) +001 703-527-3887 (outside U.S.) |
| Website | www.lpslabs.com |
| E-mail | sds@lpslabs.com |

2. Hazard(s) identification

| | | |
|------------------------------|---|-----------------------------|
| Physical hazards | Flammable aerosols | Category 1 |
| | Gases under pressure | Compressed gas |
| Health hazards | Serious eye damage/eye irritation | Category 2 |
| | Specific target organ toxicity, single exposure | Category 3 narcotic effects |
| | Aspiration hazard | Category 1 |
| Environmental hazards | Not classified. | |
| OSHA defined hazards | Not classified. | |

Label elements



| | |
|--------------------------------|--|
| Signal word | Danger |
| Hazard statement | Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes serious eye irritation. May cause drowsiness or dizziness. |
| Precautionary statement | |
| Prevention | Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye/face protection. |
| Response | If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. |
| Storage | Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. |

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|-------------------|--------------------------|------------|---------|
| Acetone | | 67-64-1 | 80 - 90 |
| Carbon Dioxide | | 124-38-9 | 5 - 10 |
| Cyclohexylmethane | | 108-87-2 | 1 - 10 |

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if symptoms occur.

Eye contact Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention immediately.

Ingestion Call a physician or poison control center immediately. Only induce vomiting at the instruction of medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain.

Indication of immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically.

General information IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Powder. Alcohol resistant foam. Water. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Scoop up used absorbent into drums or other appropriate container. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage**Precautions for safe handling**

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of the reach of children.

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

| Components | Type | Value |
|-------------------------------------|------|------------------------|
| Acetone (CAS 67-64-1) | PEL | 2400 mg/m3 1000 ppm |
| Carbon Dioxide (CAS 124-38-9) | PEL | 9000 mg/m3 |
| Cyclohexylmethane (CAS 108-87-2) | PEL | 5000 ppm 2000 mg/m3 |
| Iso amyl acetate (CAS 123-92-2) | PEL | 500 ppm 525 mg/m3 |
| Primary Amyl Acetate (CAS 628-63-7) | PEL | 100 ppm 525 mg/m3 |
| | | 100 ppm |

US. OSHA Table Z-2 (29 CFR 1910.1000)

| Components | Type | Value |
|------------------------|---------|---------|
| Toluene (CAS 108-88-3) | Ceiling | 300 ppm |
| | TWA | 200 ppm |

US. ACGIH Threshold Limit Values

| Components | Type | Value |
|---------------------------------------|------|-----------|
| 2-Methyl Butyl Acetate (CAS 624-41-9) | STEL | 100 ppm |
| | TWA | 50 ppm |
| Acetone (CAS 67-64-1) | STEL | 750 ppm |
| | TWA | 500 ppm |
| Carbon Dioxide (CAS 124-38-9) | STEL | 30000 ppm |
| | TWA | 5000 ppm |
| Cyclohexylmethane (CAS 108-87-2) | TWA | 400 ppm |
| Iso amyl acetate (CAS 123-92-2) | STEL | 100 ppm |

US. ACGIH Threshold Limit Values

| Components | Type | Value |
|-------------------------------------|------|---------|
| Primary Amyl Acetate (CAS 628-63-7) | TWA | 50 ppm |
| | STEL | 100 ppm |
| Toluene (CAS 108-88-3) | TWA | 50 ppm |
| | TWA | 20 ppm |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value |
|-------------------------------------|------|-------------------------|
| Acetone (CAS 67-64-1) | TWA | 590 mg/m3 250 ppm |
| Carbon Dioxide (CAS 124-38-9) | STEL | 54000 mg/m3 |
| | TWA | 30000 ppm 9000 mg/m3 |
| Cyclohexylmethane (CAS 108-87-2) | TWA | 5000 ppm 1600 mg/m3 |
| | TWA | 400 ppm |
| Iso amyl acetate (CAS 123-92-2) | TWA | 525 mg/m3 |
| | TWA | 100 ppm |
| Primary Amyl Acetate (CAS 628-63-7) | TWA | 525 mg/m3 |
| | TWA | 100 ppm |
| Toluene (CAS 108-88-3) | STEL | 560 mg/m3 150 ppm |
| | TWA | 375 mg/m3 |
| | TWA | 100 ppm |

Biological limit values**ACGIH Biological Exposure Indices**

| Components | Value | Determinant | Specimen | Sampling Time |
|------------------------|-----------|---------------------------|---------------------|---------------|
| Acetone (CAS 67-64-1) | 50 mg/l | Acetone | Urine | * |
| Toluene (CAS 108-88-3) | 0.3 mg/g | o-Cresol, with hydrolysis | Creatinine in urine | * |
| | 0.03 mg/l | Toluene | Urine | * |
| | 0.02 mg/l | Toluene | Blood | * |

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3)

Skin designation applies.

Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Provide eyewash station.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Do not get in eyes. Wear safety glasses with side shields (or goggles). Eye wash fountain is recommended.

Skin protection**Hand protection**

Chemical resistant gloves are recommended.

Other

Avoid contact with the skin. Wear appropriate chemical resistant clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

None known.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

| | |
|---|---|
| Appearance | Liquid. |
| Physical state | Gas. |
| Form | Aerosol. Compressed gas. |
| Color | Clear water-white |
| Odor | Ether-like. Fruity. |
| Odor threshold | Not established |
| pH | Not applicable |
| Melting point/freezing point | Not established |
| Initial boiling point and boiling range | 132.8 °F (56 °C) |
| Flash point | < 1.4 °F (< -17.0 °C) Tag Closed Cup |
| Evaporation rate | > 1 BuAc |
| Flammability (solid, gas) | Not available. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | 2.6 % |
| Flammability limit - upper (%) | 12.8 % |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | > 75 mm Hg @ 20°C |
| Vapor density | > 2 |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Soluble |
| Partition coefficient (n-octanol/water) | > 1 |
| Auto-ignition temperature | 869 °F (465 °C) |
| Decomposition temperature | Not established |
| Viscosity | < 3 cSt @ 25°C |
| Other information | |
| Heat of combustion | 25 - 30 kJ/g |
| Percent volatile | 100 % |
| Specific gravity | 0.75 - 0.77 @ 20°C |
| VOC (Weight %) | 9.4 % per US State & Federal Consumer Product Regulations |

10. Stability and reactivity

| | |
|---|---|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | Hazardous polymerization does not occur. |
| Conditions to avoid | Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| Incompatible materials | Strong oxidizing agents. |
| Hazardous decomposition products | Carbon oxides. |

11. Toxicological information

Information on likely routes of exposure

| | |
|-------------------|---|
| Ingestion | May cause discomfort if swallowed. May be fatal if swallowed and enters airways. However, ingestion is not likely to be a primary route of occupational exposure. |
| Inhalation | Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. |

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eye contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Information on toxicological effects

Acute toxicity Narcotic effects.

| Components | Species | Test Results |
|----------------------------------|----------------|--|
| Acetone (CAS 67-64-1) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | > 15800 mg/kg 20 ml/kg |
| <i>Inhalation</i> | | |
| LC50 | Rat | 55700 ppm 76 mg/l, 4 Hours 50.1 mg/l 50.1 mg/l, 8 Hours |
| <i>Oral</i> | | |
| LD50 | Mouse | 3000 mg/kg |
| | Rabbit | 5340 mg/kg |
| | Rat | 5800 mg/kg 2.2 ml/kg |
| <i>Other</i> | | |
| LD50 | Mouse | 1297 mg/kg |
| | Rat | 5500 mg/kg |
| Cyclohexylmethane (CAS 108-87-2) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rat | >= 4 ml/kg |
| <i>Inhalation</i> | | |
| LC25 | Rabbit | 7300 mg/l |
| LC50 | Rat | 16 mg/l |
| <i>Oral</i> | | |
| LD50 | Rat | > 8 ml/kg |
| Iso amyl acetate (CAS 123-92-2) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | > 5 g/kg |
| <i>Oral</i> | | |
| LD50 | Rabbit | 7400 mg/kg |
| | Rat | 16600 mg/kg |
| Toluene (CAS 108-88-3) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | > 5000 mg/kg 14.1 ml/kg |
| <i>Inhalation</i> | | |
| LC50 | Mouse | 6405 - 7436 ppm 5320 mg/l, 8 Hours |

| Components | Species | Test Results |
|---|--|---------------------|
| | | 400 mg/l, 24 Hours |
| | Rat | 26700 mg/l, 1 Hours |
| | | 12200 mg/l, 2 Hours |
| | | 8000 mg/l, 4 Hours |
| | | 5879 - 6281 ppm |
| | | 25.7 mg/l |
| <i>Oral</i> | | |
| LD50 | Rat | 2.6 g/kg |
| <i>Other</i> | | |
| LD50 | Mouse | 59 mg/kg |
| | Rat | 1332 mg/kg |
| Skin corrosion/irritation | Based on available data, the classification criteria are not met. | |
| Serious eye damage/eye irritation | Causes serious eye irritation. | |
| Respiratory or skin sensitization | | |
| Respiratory sensitization | Based on available data, the classification criteria are not met. | |
| Skin sensitization | This product is not expected to cause skin sensitization. | |
| Germ cell mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. | |
| Carcinogenicity | This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. | |
| ACGIH Carcinogens | | |
| Acetone (CAS 67-64-1) | A4 Not classifiable as a human carcinogen. | |
| Toluene (CAS 108-88-3) | A4 Not classifiable as a human carcinogen. | |
| IARC Monographs. Overall Evaluation of Carcinogenicity | | |
| Toluene (CAS 108-88-3) | 3 Not classifiable as to carcinogenicity to humans. | |
| OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) | | |
| Not listed. | | |
| Reproductive toxicity | This product is not expected to cause reproductive or developmental effects. | |
| Specific target organ toxicity - single exposure | May cause drowsiness or dizziness. | |
| Specific target organ toxicity - repeated exposure | Based on available data, the classification criteria are not met. | |
| Aspiration hazard | May be fatal if swallowed and enters airways. | |
| Chronic effects | Prolonged inhalation may be harmful. | |

12. Ecological information

Ecotoxicity Ecological injuries are not known or expected under normal use.

| Components | Species | Test Results |
|-------------------------------------|---------|---|
| Acetone (CAS 67-64-1) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia magna) 10294 - 17704 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout, donaldson trout (Oncorhynchus mykiss) 4740 - 6330 mg/l, 96 hours |
| Cyclohexylmethane (CAS 108-87-2) | | |
| Aquatic | | |
| Fish | LC50 | Striped bass (Morone saxatilis) 5.8 mg/l, 96 hours |
| Primary Amyl Acetate (CAS 628-63-7) | | |
| Aquatic | | |
| Fish | LC50 | Western mosquitofish (Gambusia affinis) 65 mg/l, 96 hours |

| Components | Species | Test Results |
|--|--|--|
| Toluene (CAS 108-88-3) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia magna) 5.46 - 9.83 mg/l, 48 hours |
| Fish | LC50 | Coho salmon,silver salmon (Oncorhynchus kisutch) 8.11 mg/l, 96 hours |
| Persistence and degradability | Not inherently biodegradable. | |
| Bioaccumulative potential | Not available. | |
| Partition coefficient n-octanol / water (log Kow) | | |
| LPS® U-10 | | > 1 |
| Acetone | | -0.24 |
| Cyclohexylmethane | | 3.61 |
| Primary Amyl Acetate | | 2.3 |
| Toluene | | 2.73 |
| Mobility in soil | No data available. | |
| Other adverse effects | None known. | |
| 13. Disposal considerations | | |
| Disposal instructions | Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations. | |
| Local disposal regulations | Dispose in accordance with all applicable regulations. | |
| Hazardous waste code | D001: Waste Flammable material with a flash point <140 F D003: Waste Reactive material | |
| Waste from residues / unused products | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). | |
| Contaminated packaging | Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers. | |
| 14. Transport information | | |
| DOT | | |
| UN number | UN1950 | |
| UN proper shipping name | Aerosols, flammable | |
| Transport hazard class(es) | | |
| Class | 2.1 | |
| Subsidiary risk | - | |
| Label(s) | 2.1 | |
| Packing group | Not applicable. | |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. | |
| Special provisions | N82 | |
| Packaging exceptions | 306 | |
| Packaging non bulk | None | |
| Packaging bulk | None | |
| IATA | | |
| UN number | UN1950 | |
| UN proper shipping name | Aerosols, flammable | |
| Transport hazard class(es) | | |
| Class | 2.1 | |
| Subsidiary risk | - | |
| Packing group | Not applicable. | |
| Environmental hazards | No | |
| ERG Code | 10L | |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. | |
| Other information | | |
| Passenger and cargo aircraft | Allowed. | |

Cargo aircraft only Allowed.

IMDG

UN number UN1950
UN proper shipping name AEROSOLS, flammable
Transport hazard class(es)
Class 2.1
Subsidiary risk -
Packing group Not applicable.
Environmental hazards
Marine pollutant No
EmS F-D, S-U
Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

| | |
|-------------------------------------|---------|
| Acetone (CAS 67-64-1) | Listed. |
| Iso amyl acetate (CAS 123-92-2) | Listed. |
| Primary Amyl Acetate (CAS 628-63-7) | Listed. |
| Toluene (CAS 108-88-3) | Listed. |

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

| | |
|--------------------------|------------------------|
| Hazard categories | Immediate Hazard - Yes |
| | Delayed Hazard - No |
| | Fire Hazard - Yes |
| | Pressure Hazard - Yes |
| | Reactivity Hazard - No |

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes**SARA 313 (TRI reporting)**

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

Acetone (CAS 67-64-1) 6532

Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 % weight/volumn

Toluene (CAS 108-88-3) 35 % weight/volumn

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

Toluene (CAS 108-88-3) 594

US state regulations**US. Massachusetts RTK - Substance List**

Acetone (CAS 67-64-1)

Carbon Dioxide (CAS 124-38-9)

Cyclohexylmethane (CAS 108-87-2)

Iso amyl acetate (CAS 123-92-2)

Primary Amyl Acetate (CAS 628-63-7)

Toluene (CAS 108-88-3)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Carbon Dioxide (CAS 124-38-9)

Cyclohexylmethane (CAS 108-87-2)

Iso amyl acetate (CAS 123-92-2)

Primary Amyl Acetate (CAS 628-63-7)

Toluene (CAS 108-88-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

Carbon Dioxide (CAS 124-38-9)

Cyclohexylmethane (CAS 108-87-2)

Iso amyl acetate (CAS 123-92-2)

Primary Amyl Acetate (CAS 628-63-7)

Toluene (CAS 108-88-3)

US. Rhode Island RTK

Acetone (CAS 67-64-1)

Iso amyl acetate (CAS 123-92-2)

Primary Amyl Acetate (CAS 628-63-7)

Toluene (CAS 108-88-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3) Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3) Listed: August 7, 2009

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | Yes |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | No |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 04-18-2014
Revision date 04-18-2014
Version # 02

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision Information

Composition / Information on Ingredients: Ingredients
Transport Information: Material Transportation Information
Regulatory Information: Risk Phrases - Labeling
GHS: Classification