

TDS0006 Established: 17 Jun 1987 Updated: 07 Mar 2017

TECHNICAL DATA SHEET FOR

ANTI-FUNGUS SOLUTION

DESCRIPTION	:	Anti-fungus Solution is used for surface preparation prior to painting to get rid of fungus growth and to kill any remaining fungus spores left on the substrate, so as to prevent the spore from germination
ТҮРЕ	:	Water-based fungicidal wash
COLOUR	:	Colourless
FINISH	:	Not applicable
USES	:	Anti-fungus Solution is used in surface wash for masonry, brick, wood and plastering surfaces prior to painting
FEATURES	:	Fast killing actionCovers a wide spectrum of fungus and algaeEasy application
APPLICATION DATA		
METHOD	:	Brush, roller or air spray
THEORETICAL COVERAGE	:	$4 - 8 \text{ m}^2$ / litre (depend on substrate porosity)
DILUTION	:	Not required
SURFACE PREPARATION	:	 Wash surface with water and remove unstable matter or organism as much as possible either by brushing, scrubbing or high jet washing Apply Anti-Fungus Solution and leave on for 1 day Wash surface again using brushing, scrubbing or high jet washing to remove the dead organism Allow surface to dry thoroughly before painting
DRYING TIME	:	Not applicable
OVERCOATING TIME	:	Not applicable
RECOMMENDED PAINTING SYSTEM	:	Not applicable
CLEANING	:	All equipments should be cleaned with water immediately after use

ANTI-FUNGUS SOLUTION

GENERAL INFORMATION

SOLID CONTENT	:	Not applicable
SPECIFIC GRAVITY	•	0.98 ± 3.0 % kg / litre
PACKING	:	5 litres and 20 litres
STORAGE	:	Store in a tightly sealed container in a cool, dry place
SHELF LIFE	:	Up to 12 months in a tightly sealed container
PRECAUTION	:	Ensure good ventilation during application and drying of paint. Avoid direct contact with sensitive skin. Use appropriate personal protective equipment
		Refer to the product Safety Data Sheet for more information

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

Enquiries / Contact Details : Customer Service 6265 5355 (Main Line) 6264 1603 (Fax) www.nipponpaint.com.sg